



March 24, 2008

MODEL #	MANUFACTURER #	DESCRIPTION	MSRP
AX-6030	6030	BELL CUT-OFF 6VDC OR 12VDC, 5 AMP/120VAC FORM "C" CONTACTS	35.56
AX-6062	6062	MULTI-FUNCTION TIMER, 12VDC OR 24VDC OPERATION. 1 SEC. TO 60 MIN. ADJUSTABLE TIMING RANGE. ONE SECOND MOMENTARY RELAY A	47.41
AX-ACM8	ACM8	UL RECOGNIZED ACCESS POWER CONTROLLER. EIGHT (8) FUSE PROTECTED ACCESS CONTROL SYSTEM OUTPUTS WITH FACP INTERFACE FOR A	187.59
AX-ACM8CB	ACM8CB	UL RECOGNIZED ACCESS POWER CONTROLLER. EIGHT (8) PTC PROTECTED ACCESS CONTROL SYSTEM OUTPUTS WITH FACP INTERFACE FOR AC	187.59
AX-ACM8CBE	ACM8CBE	ACCESS POWER CONTROLLER. EIGHT (8) PTC PROTECTED ACCESS CONTROL SYSTEM OUTPUTS WITH FACP INTERFACE FOR ACCESS CONTROL A	282.83
AX-ACM8E	ACM8E	ACCESS POWER CONTROLLER. EIGHT (8) FUSE PROTECTED ACCESS CONTROL SYSTEM OUTPUTS WITH FACP INTERFACE FOR ACCESS CONTROL	282.83
AX-AL1002UL2ADA	AL1002UL2ADA	NAC POWER EXTENDER - 24VDC @ 10 AMP. TWO (2) CLASS A OR FOUR (4) CLASS B NAC CIRCUITS. OPERATES 2-WIRE HORN/STROBES. GE	819.44
AX-AL1002ULADA	AL1002ULADA	NAC POWER EXTENDER - 24VDC @ 10 AMP. TWO (2) CLASS A OR FOUR (4) CLASS B NAC CIRCUITS. OPERATES 2-WIRE HORN/STROBES. GE	819.44
AX-AL1002ULADAJ	AL1002ULADAJ	SAME FEATURES AS AL1002ULADA IN LARGER ENCLOSURE 18"H X 14.5"W X 4.625"D.	852.78
AX-AL100UL	AL100UL	12VDC @ 0.75 AMP, CLASS 2 POWER LIMITED OUTPUT, GREY ENCLOSURE 8.5"H X 7.5"W X 3.5"D. UL LISTED (UL603), ULC.	147.19
AX-AL1012ULACM	AL1012ULACM	ACCESS POWER CONTROLLER PROVIDING A TOTAL OF EIGHT (8) FUSE PROTECTED FAIL-SAFE AND/OR FAIL-SECURE NON-POWER LIMITED OU	747.22
AX-AL1012ULACMCB	AL1012ULACMCB	ACCESS POWER CONTROLLER PROVIDING A TOTAL OF EIGHT (8) PTC PROTECTED FAIL-SAFE AND/OR FAIL-SECURE CLASS 2 RATED POWER L	747.22
AX-AL1012ULACMCBJ	AL1012ULACMCBJ	SAME FEATURES AS AL1012ULACMCB IN LARGER ENCLOSURE 18"H X 14.5"W X 4.625"D.	783.33
AX-AL1012ULACMJ	AL1012ULACMJ	SAME FEATURES AS AL1012ULACM IN LARGER ENCLOSURE 18"H X 14.5"W X 4.625"D.	783.33
AX-AL1012ULM	AL1012ULM	12VDC @ 10 AMP, 115VAC INPUT, AC AND BATTERY MONITORING. FIRE ALARM INTERFACE. FIVE (5) INDIVIDUALLY PTC PROTECTED CLAS	713.89

AX-AL1012ULX	AL1012ULX	12VDC @ 10 AMP, 115VAC INPUT, AC AND BATTERY MONITORING, NON-POWER LIMITED OUTPUT, GREY ENCLOSURE 15.5"H X 12"W X 4.5"D	625.00
AX-AL1012ULXB	AL1012ULXB	12VDC @ 10 AMP, 115VAC INPUT, AC AND BATTERY MONITORING. NON-POWER LIMITED OUTPUT. UL RECOGNIZED COMPONENT.	525.25
AX-AL1012ULXPD16	AL1012ULXPD16	12VDC @ 10 AMP, 115VAC INPUT, AC AND BATTERY MONITORING. SIXTEEN (16) FUSE PROTECTED OUTPUTS, GREY ENCLOSURE 15.5"H X 12"W X 4.5"D	788.89
AX-AL1012ULXPD16CB	AL1012ULXPD16CB	12VDC @ 10 AMP, 115VAC INPUT, AC AND BATTERY MONITORING. SIXTEEN (16) PTC PROTECTED CLASS 2 RATED POWER LIMITED OUTPUTS	788.89
AX-AL1012ULXPD4	AL1012ULXPD4	12VDC @ 10 AMP, 115VAC INPUT, AC AND BATTERY MONITORING. FOUR (4) FUSE PROTECTED OUTPUTS, GREY ENCLOSURE 15.5"H X 12"W X 4.5"D	697.22
AX-AL1012ULXPD4CB	AL1012ULXPD4CB	12VDC @ 10 AMP, 115VAC INPUT, AC AND BATTERY MONITORING. FOUR (4) PTC PROTECTED CLASS 2 RATED POWER LIMITED OUTPUTS, GR	697.22
AX-AL1012ULXPD8	AL1012ULXPD8	12VDC @ 10 AMP, 115VAC INPUT, AC AND BATTERY MONITORING. EIGHT (8) FUSE PROTECTED OUTPUTS, GREY ENCLOSURE 15.5"H X 12"W X 4.5"D	708.33
AX-AL1012ULXPD8CB	AL1012ULXPD8CB	12VDC @ 10 AMP, 115VAC INPUT, AC AND BATTERY MONITORING. EIGHT (8) PTC PROTECTED CLASS 2 RATED POWER LIMITED OUTPUTS, G	708.33
AX-AL1024ULACM	AL1024ULACM	ACCESS POWER CONTROLLER PROVIDING A TOTAL OF EIGHT (8) FUSE PROTECTED FAIL-SAFE AND/OR FAIL-SECURE NON-POWER LIMITED OU	866.67
AX-AL1024ULACMCB	AL1024ULACMCB	ACCESS POWER CONTROLLER PROVIDING A TOTAL OF EIGHT (8) PTC PROTECTED FAIL-SAFE AND/OR FAIL-SECURE CLASS 2 RATED POWER L	866.67
AX-AL1024ULACMCBJ	AL1024ULACMCBJ	SAME FEATURES AS AL1024ULACMCB IN LARGER ENCLOSURE 18"H X 14.5"W X 4.625"D.	902.78
AX-AL1024ULACMJ	AL1024ULACMJ	SAME FEATURES AS AL1024ULACM IN LARGER ENCLOSURE 18"H X 14.5"W X 4.625"D.	902.78
AX-AL1024ULM	AL1024ULM	24VDC @ 10 AMP, 115VAC INPUT, AC AND BATTERY MONITORING. FIRE ALARM INTERFACE. FIVE (5) INDIVIDUALLY PTC PROTECTED CLAS	833.33
AX-AL1024ULMR	AL1024ULMR	SAME FEATURES AS AL1024ULM WITH RED ENCLOSURE.	833.33
AX-AL1024ULX	AL1024ULX	24VDC @ 10 AMP, 115VAC INPUT, AC AND BATTERY MONITORING, NON-POWER LIMITED OUTPUT, GREY ENCLOSURE 15.5"H X 12"W X 4.5"D	744.44
AX-AL1024ULXB	AL1024ULXB	24VDC @ 10 AMP 115VAC INPUT. AC FAIL AND BATTERY MONITORING. NON-POWER LIMITED OUTPUT. UL RECOGNIZED COMPONENT	566.67
AX-AL1024ULXPD16	AL1024ULXPD16	24VDC @ 10 AMP, 115VAC INPUT, AC AND BATTERY MONITORING. SIXTEEN (16) FUSE PROTECTED OUTPUTS, GREY ENCLOSURE 15.5"H X 12"W X 4.5"D	916.67
AX-AL1024ULXPD16CB	AL1024ULXPD16CB	24VDC @ 10 AMP, 115VAC INPUT, AC AND BATTERY MONITORING. SIXTEEN (16) PTC PROTECTED CLASS 2 RATED POWER LIMITED OUTPUTS	916.67

AX-AL1024ULXPD4	AL1024ULXPD4	24VDC @ 10 AMP, 115VAC INPUT, AC AND BATTERY MONITORING. FOUR (4) FUSE PROTECTED OUTPUTS, GREY ENCLOSURE 15.5â€H X 12â€W	816.67
AX-AL1024ULXPD4CB	AL1024ULXPD4CB	24VDC @ 10 AMP, 115VAC INPUT, AC AND BATTERY MONITORING. FOUR (4) PTC PROTECTED CLASS 2 RATED POWER LIMITED OUTPUTS, GR	816.67
AX-AL1024ULXPD8	AL1024ULXPD8	24VDC @ 10 AMP, 115VAC INPUT, AC AND BATTERY MONITORING. EIGHT (8) FUSE PROTECTED OUTPUTS, GREY ENCLOSURE 15.5â€H X 12â€W	830.56
AX-AL1024ULXPD8CB	AL1024ULXPD8CB	24VDC @ 10 AMP, 115VAC INPUT, AC AND BATTERY MONITORING. EIGHT (8) PTC PROTECTED CLASS 2 RATED POWER LIMITED OUTPUTS, G	830.56
AX-AL1024ULXR	AL1024ULXR	SAME FEATURES AS AL1024ULX WITH RED ENCLOSURE.	744.44
AX-AL1042UL2ADA	AL1042UL2ADA	NAC POWER EXTENDER - 24VDC @ 10 AMP. FOUR (4) CLASS A OR FOUR (4) CLASS B NAC CIRCUITS. OPERATES 2-WIRE HORN/STROBES. G	936.11
AX-AL1042ULADA	AL1042ULADA	NAC POWER EXTENDER - 24VDC @ 10 AMP. FOUR (4) CLASS A OR FOUR (4) CLASS B NAC CIRCUITS. OPERATES 2-WIRE HORN/STROBES. G	936.11
AX-AL125UL	AL125UL	12VDC OR 24VDC @ 1 AMP, LATCHING/NON LATCHING FIRE ALARM DISCONNECT, GREY ENCLOSURE 8.5"H X 7.5"W X 3.5"D AND OPEN FRAM	167.39
AX-AL125ULB	AL125ULB	12VDC OR 24VDC @ 1 AMP, LATCHING/NON-LATCHING FIRE ALARM DISCONNECT. UL RECOGNIZED COMPONENT.	97.78
AX-AL125ULE	AL125ULE	12VDC @ 1 AMP, OR 24VDC @ .5 AMP. LATCHING/NON LATCHING FIRE ALARM DISCONNECT, GREY ENCLOSURE 13.5"H X 13"W X 3.25"D CA	142.22
AX-AL125ULP	AL125ULP	12VDC @ 1 AMP OR 24VDC @ .5 AMP, LATCHING/NON LATCHING FIRE ALARM DISCONNECT, GREY ENCLOSURE 8.5H X 7.5"W X 3.5"D, TP24	167.39
AX-AL125ULX	AL125ULX	12VDC OR 24VDC @ 1 AMP, LATCHING/NON LATCHING FIRE ALARM DISCONNECT, RED ENCLOSURE 13.5"H X 13"W X 3.25"D AND OPEN FRAM	199.13
AX-AL175UL	AL175UL	12VDC OR 24VDC @ 1.75 AMP, LATCHING/NON LATCHING FIRE ALARM DISCONNECT, GREY ENCLOSURE 8.5"H X 7.5"W X 3.5"D, UL/CUL LI	233.77
AX-AL175ULB	AL175ULB	12VDC OR 24VDC @ 1.75 AMP, LATCHING/NON-LATCHING FIRE ALARM DISCONNECT. UL RECOGNIZED COMPONENT.	139.26
AX-AL175ULX	AL175ULX	SAME FEATURES AS AL175UL IN LARGER ENCLOSURE 13.5"H X 13"W X 3.25"D.	265.51
AX-AL175ULX2	AL175ULX2	12VDC OR 24VDC @ 1.75 AMP LATCHING FIRE ALARM DISCONNECT W/RESET, CLASS 2 RATED POWER LIMITED OUTPUT, GREY ENCLOSURE 13	372.29
AX-AL176UL	AL176UL	12VDC OR 24 VDC @ 1.75 AMP, 115VAC INPUT, AC AND BATTERY MONITORING, CLASS 2 RATED POWER LIMITED OUTPUT, GREY ENCLOSURE	233.77
AX-AL176ULB	AL176ULB	12 VDC OR 24 VDC @ 1.75 AMP BOARD, AC FAIL AND LOW BATTERY REPORTING. UL RECOGNIZED COMPONENT	139.26
AX-AL176ULX	AL176ULX	SAME FEATURES AS AL176UL IN LARGER ENCLOSURE 13.5"H X 13"W X 3.25"D.	265.51

AX-AL201UL	AL201UL	12VDC @ 1.75 AMP, 115VAC INPUT, AC AND BATTERY MONITORING, CLASS 2 RATED POWER LIMITED OUTPUT, GREY ENCLOSURE 8.5â€H X 7	187.59
AX-AL201ULB	AL201ULB	12VDC OR 24VDC @ 1.75 AMP, AC AND BATTERY MONITORING. UL RECOGNIZED COMPONENT.	139.26
AX-AL300ULB	AL300ULB	12VDC OR 24VDC @ 2.5 AMP, AC AND BATTERY MONITORING, CLASS 2 RATED POWER LIMITED OUTPUT. UL RECOGNIZED COMPONENT.	170.27
AX-AL300ULM	AL300ULM	12VDC OR 24VDC @ 2.5 AMP, 115VAC INPUT, AC AND BATTERY MONITORING. FIRE ALARM INTERFACE. FIVE (5) INDIVIDUALLY PTC PROT	430.01
AX-AL300ULMR	AL300ULMR	SAME FEATURES AS AL300ULM WITH RED ENCLOSURE.	430.01
AX-AL300ULPD4	AL300ULPD4	12VDC OR 24VDC @ 2.5 AMP, 115VAC INPUT, AC AND BATTERY MONITORING. FOUR (4) FUSE PROTECTED CLASS 2 RATED POWER LIMITED	412.70
AX-AL300ULPD4CB	AL300ULPD4CB	12VDC OR 24VDC @ 2.5 AMP, 115VAC INPUT, AC AND BATTERY MONITORING. FOUR (4) PTC PROTECTED CLASS 2 RATED POWER LIMITED O	412.70
AX-AL300ULPD8	AL300ULPD8	12VDC OR 24VDC @ 2.5 AMP, 115VAC INPUT, AC AND BATTERY MONITORING. EIGHT (8) FUSE PROTECTED CLASS 2 RATED POWER LIMITED	424.24
AX-AL300ULPD8CB	AL300ULPD8CB	12VDC OR 24VDC @ 2.5 AMP, 115VAC INPUT, AC AND BATTERY MONITORING. EIGHT (8) PTC PROTECTED CLASS 2 RATED POWER LIMITED	424.24
AX-AL300ULX	AL300ULX	12VDC OR 24VDC @ 2.5 AMP, 115VAC INPUT, AC AND BATTERY MONITORING, CLASS 2 RATED POWER LIMITED OUTPUT, GREY ENCLOSURE 1	337.66
AX-AL300ULXB	AL300ULXB	12VDC OR 24VDC @ 2.5 AMP, 115VAC INPUT, AC AND BATTERY MONITORING, CLASS 2 RATED POWER LIMITED OUTPUT. UL RECOGNIZED CO	248.20
AX-AL300ULXD	AL300ULXD	12VDC OR 24VDC @ 2.5 AMP, 115VAC OR 220VAC INPUT, AC AND BATTERY MONITORING, CLASS 2 RATED POWER LIMITED OUTPUT, GREY E	369.41
AX-AL300ULXPD16	AL300ULXPD16	12VDC OR 24VDC @ 2.5 AMP, 115VAC INPUT, AC AND BATTERY MONITORING. SIXTEEN (16) FUSE PROTECTED CLASS 2 RATED POWER LIM I	510.82
AX-AL300ULXPD16CB	AL300ULXPD16CB	12VDC OR 24VDC @ 2.5 AMP, 115VAC INPUT, AC AND BATTERY MONITORING. SIXTEEN (16) PTC PROTECTED CLASS 2 RATED POWER LIMIT	510.82
AX-AL300ULXR	AL300ULXR	SAME FEATURES AS AL300ULX WITH RED ENCLOSURE.	337.66
AX-AL400UL	AL400UL	12VDC @ 4 AMP OR 24VDC @ 3 AMP, 115VAC INPUT, AC AND BATTERY MONITORING, CLASS 2 RATED POWER LIMITED OUTPUT, GREY ENCLO	375.18
AX-AL400UL3	AL400UL3	SIMULTANEOUS POWER OUTPUTS: 5VDC @ 1.75 AMP, 12VDC @ 1.75 AMP AND 24VDC @ 1.5 AMP, 115VAC INPUT, AC AND BATTERY MONITOR	545.45
AX-AL400UL3X	AL400UL3X	SAME FEATURES AS AL400UL3 IN LARGER ENCLOSURE 15.5â€H X 12â€W X 4.5â€D.	555.56
AX-AL400ULACM	AL400ULACM	ACCESS POWER CONTROLLER PROVIDING A TOTAL OF EIGHT (8) FUSE PROTECTED FAIL-SAFE AND/OR FAIL-SECURE CLASS 2 RATED POWER	548.34

AX-AL400ULACMCB	AL400ULACMCB	ACCESS POWER CONTROLLER PROVIDING A TOTAL OF EIGHT (8) PTC PROTECTED FAIL-SAFE AND/OR FAIL-SECURE CLASS 2 RATED POWER L	548.34
AX-AL400ULACMCBJ	AL400ULACMCBJ	SAME FEATURES AS AL400ULACMCB IN LARGER ENCLOSURE 18"H X 14.5"W X 4.625"D.	563.89
AX-AL400ULACMJ	AL400ULACMJ	SAME FEATURES AS AL400ULACM IN LARGER ENCLOSURE 18"H X 14.5"W X 4.625"D.	563.89
AX-AL400ULADA	AL400ULADA	NAC POWER EXTENDER, 24VDC OR 12VDC @ 4 AMP, 115VAC INPUT, COMPATIBLE WITH CLASS B CIRCUITS, ONE OUTPUT, RED ENCLOSURE 1	554.11
AX-AL400ULB	AL400ULB	12VDC @ 4 AMP OR 24VDC @ 3 AMP, AC AND BATTERY MONITORING, CLASS 2 RATED POWER LIMITED OUTPUT. UL RECOGNIZED COMPONENT.	222.22
AX-AL400ULM	AL400ULM	12VDC @ 4 AMP OR 24VDC @ 3 AMP, 115VAC INPUT, AC AND BATTERY MONITORING. FIRE ALARM INTERFACE . FIVE (5) INDIVIDUALLY P	513.71
AX-AL400ULMR	AL400ULMR	SAME FEATURES AS AL400ULM WITH RED ENCLOSURE.	513.71
AX-AL400ULPD4	AL400ULPD4	12VDC @ 4 AMP OR 24VDC @ 3 AMP, 115VAC INPUT, AC AND BATTERY MONITORING. FOUR (4) FUSE PROTECTED CLASS 2 RATED POWER LI	470.42
AX-AL400ULPD4CB	AL400ULPD4CB	12VDC @ 4 AMP OR 24VDC @ 3 AMP, 115VAC INPUT, AC AND BATTERY MONITORING. FOUR (4) PTC PROTECTED CLASS 2 RATED POWER LIM	470.42
AX-AL400ULPD8	AL400ULPD8	12VDC @ 4 AMP OR 24VDC @ 3 AMP, 115VAC INPUT, AC AND BATTERY MONITORING. EIGHT (8) FUSE PROTECTED CLASS 2 RATED POWER L	481.96
AX-AL400ULPD8CB	AL400ULPD8CB	12VDC @ 4 AMP OR 24VDC @ 3 AMP, 115VAC INPUT, AC AND BATTERY MONITORING. EIGHT (8) PTC PROTECTED CLASS 2 RATED POWER LI	481.96
AX-AL400ULX	AL400ULX	12VDC @ 4 AMP OR 24VDC @ 3 AMP, 115VAC INPUT, AC AND BATTERY MONITORING, CLASS 2 RATED POWER LIMITED OUTPUT, GREY ENCLO	421.36
AX-AL400ULXB	AL400ULXB	12VDC @ 4 AMP OR 24VDC @ 3 AMP, 115VAC INPUT, AC AND BATTERY MONITORING, CLASS 2 RATED POWER LIMITED OUTPUT. UL RECOGNI	294.37
AX-AL400ULXPD16	AL400ULXPD16	12VDC @ 4 AMP OR 24VDC @ 3 AMP, 115VAC INPUT, AC AND BATTERY MONITORING. SIXTEEN (16) FUSE PROTECTED CLASS 2 RATED POWE	572.22
AX-AL400ULXPD16CB	AL400ULXPD16CB	12VDC @ 4 AMP OR 24VDC @ 3 AMP, 115VAC INPUT, AC AND BATTERY MONITORING. SIXTEEN (16) PTC PROTECTED CLASS 2 RATED POWER	572.22
AX-AL400ULXR	AL400ULXR	SAME FEATURES AS AL400ULX WITH RED ENCLOSURE.	421.36
AX-AL600UL3	AL600UL3	SIMULTANEOUS POWER OUTPUTS: 5VDC AND 12VDC @ 1.75 AMP, AND 24VDC @ 3 AMP, 115VAC INPUT, AC AND BATTERY MONITORING. TWO	700.00
AX-AL600UL3X	AL600UL3X	SAME FEATURES AS AL600UL3 IN LARGER ENCLOSURE 15.5â€H X 12â€W X 4.5â€D.	730.56
AX-AL600ULACM	AL600ULACM	ACCESS POWER CONTROLLER PROVIDING A TOTAL OF EIGHT (8) FUSE PROTECTED FAIL-SAFE AND/OR FAIL-SECURE NON-POWER LIMITED OU	702.78

AX-AL600ULACMCB	AL600ULACMCB	ACCESS POWER CONTROLLER PROVIDING A TOTAL OF EIGHT (8) PTC PROTECTED FAIL-SAFE AND/OR FAIL-SECURE CLASS 2 RATED POWER L	702.78
AX-AL600ULACMCBJ	AL600ULACMCBJ	SAME FEATURES AS AL600ULACMCB IN LARGER ENCLOSURE 18"H X 14.5"W X 4.625"D.	738.89
AX-AL600ULACMJ	AL600ULACMJ	SAME FEATURES AS AL600ULACM IN LARGER ENCLOSURE 18"H X 14.5"W X 4.625"D.	738.89
AX-AL600ULADA	AL600ULADA	NAC POWER EXTENDER, 24VDC OR 12VDC @ 6.5 AMP, TWO (2) CLASS A OR FOUR (4) CLASS B OUTPUTS, 115VAC INPUT, INPUT TO OUTPU	611.11
AX-AL600ULADAJ	AL600ULADAJ	SAME FEATURES AS AL600ULADA IN LARGER ENCLOSURE 18"H X 14.5"W X 4.625"D.	647.22
AX-AL600ULB	AL600ULB	12VDC OR 24VDC @ 6 AMP, AC AND BATTERY MONITORING, NON-POWER LIMITED OUTPUT. UL RECOGNIZED COMPONENT.	265.51
AX-AL600ULM	AL600ULM	12VDC OR 24VDC @ 6 AMP, 115VAC INPUT, AC AND BATTERY MONITORING. FIRE ALARM INTERFACE. FIVE (5) INDIVIDUALLY PTC PROTEC	669.44
AX-AL600ULMR	AL600ULMR	SAME FEATURES AS AL600ULM WITH RED ENCLOSURE.	669.44
AX-AL600ULPD4	AL600ULPD4	12VDC OR 24VDC @ 6 AMP, 115VAC INPUT, AC AND BATTERY MONITORING. FOUR (4) FUSE PROTECTED OUTPUTS, GREY ENCLOSURE 13.5"â€œH	652.78
AX-AL600ULPD4CB	AL600ULPD4CB	12VDC OR 24VDC @ 6 AMP, 115VAC INPUT, AC AND BATTERY MONITORING. FOUR (4) PTC PROTECTED CLASS 2 RATED POWER LIMITED OUT	652.78
AX-AL600ULPD8	AL600ULPD8	12VDC OR 24VDC @ 6 AMP, 115VAC INPUT, AC AND BATTERY MONITORING. EIGHT (8) FUSE PROTECTED OUTPUTS, GREY ENCLOSURE 13.5"â€œH	663.89
AX-AL600ULPD8CB	AL600ULPD8CB	12VDC OR 24VDC @ 6 AMP, 115VAC INPUT, AC AND BATTERY MONITORING. EIGHT (8) PTC PROTECTED CLASS 2 RATED POWER LIMITED OU	663.89
AX-AL600ULX	AL600ULX	12VDC OR 24VDC @ 6 AMP, 115VAC INPUT, AC AND BATTERY MONITORING, NON-POWER LIMITED OUTPUT, GREY ENCLOSURE 13.5"â€œH X 13"â€œW	580.56
AX-AL600ULXB	AL600ULXB	12VDC OR 24VDC @ 6 AMP, 115VAC INPUT, AC AND BATTERY MONITORING, NON-POWER LIMITED OUTPUT. UL RECOGNIZED COMPONENT.	464.65
AX-AL600ULXD	AL600ULXD	12VDC OR 24VDC @ 6 AMP, 115VAC OR 220VAC INPUT, AC AND BATTERY MONITORING, NON-POWER LIMITED OUTPUT, GREY ENCLOSURE 15.	611.11
AX-AL600ULXPD16	AL600ULXPD16	12VDC OR 24VDC @ 6 AMP, 115VAC INPUT, AC AND BATTERY MONITORING. SIXTEEN (16) FUSE PROTECTED OUTPUTS, GREY ENCLOSURE 15	747.22
AX-AL600ULXPD16CB	AL600ULXPD16CB	12VDC OR 24VDC @ 6 AMP, 115VAC INPUT, AC AND BATTERY MONITORING. SIXTEEN (16) PTC PROTECTED CLASS 2 RATED POWER LIMITED	747.22
AX-AL600ULXR	AL600ULXR	SAME FEATURES AS AL600ULX WITH RED ENCLOSURE.	580.56
AX-AL602UL2ADA	AL602UL2ADA	NAC POWER EXTENDER - 24VDC OR 12VDC @ 6.5 AMP. TWO (2) CLASS A OR FOUR (4) CLASS B NAC CIRCUITS. OPERATES 2-WIRE HORN/S	625.00

AX-AL602ULADA	AL602ULADA	NAC POWER EXTENDER - 24VDC OR 12VDC @ 6.5 AMP. TWO (2) CLASS A OR FOUR (4) CLASS B NAC CIRCUITS. OPERATES 2-WIRE HORN/S	625.00
AX-AL602ULADAJ	AL602ULADAJ	SAME FEATURES AS AL602ULADA IN LARGER ENCLOSURE 18"H X 14.5"W X 4.625"D.	661.11
AX-AL624	AL624	6VDC, 12VDC @ 1.2 AMP OR 24VDC @ 750MA.	32.59
AX-AL62412C	AL62412C	6VDC @ 1.2 AMP, 12VDC/4AH BATTERY & 16.5VAC/20VA PLUG-IN TRANSFORMER.	115.56
AX-AL62412CX	AL62412CX	6VDC @ 1.2 AMP, 12VDC/7AH BATTERY & 16.5VAC/20VA PLUG-IN TRANSFORMER.	124.44
AX-AL62424C	AL62424C	24VDC @ 750MA , TWO (2) 12VDC/4AH BATTERIES & 24VAC/40VA PLUG-IN TRANSFORMER.	164.50
AX-AL624E	AL624E	6VDC, 12VDC @ 1.2 AMP OR 24VDC @ 750MA , GREY ENCLOSURE 8.5"H X 7.5"W X 3.5"D.	82.96
AX-AL624ET	AL624ET	6VDC, 12VDC @ 1.2 AMP OR 24VDC @ 750MA , 16VAC/20VA PLUG-IN TRANSFORMER, GREY ENCLOSURE 8.5"H X 7.5"W X 3.5"D.	100.74
AX-AL642UL2ADA	AL642UL2ADA	NAC POWER EXTENDER - 24VDC OR 12VDC @ 6.5 AMP. FOUR (4) CLASS A OR FOUR (4) CLASS B NAC CIRCUITS. OPERATES 2-WIRE HORN/	819.44
AX-AL642ULADA	AL642ULADA	NAC POWER EXTENDER - 24VDC OR 12VDC @ 6.5 AMP. FOUR (4) CLASS A OR FOUR (4) CLASS B NAC CIRCUITS. OPERATES 2-WIRE HORN/	819.44
AX-AL800ULADA	AL800ULADA	NAC POWER EXTENDER, 24VDC OR 12VDC @ 8 AMP, TWO (2) CLASS A OR FOUR (4) CLASS B OUTPUTS, 115VAC INPUT, INPUT TO OUTPUT	694.44
AX-AL800ULADAJ	AL800ULADAJ	SAME FEATURES AS AL800ULADAJ IN LARGER ENCLOSURE 18"H X 14.5"W X 4.625"D.	730.56
AX-AL802UL2ADA	AL802UL2ADA	NAC POWER EXTENDER - 24VDC OR 12VDC @ 8 AMP. TWO (2) CLASS A OR FOUR (4) CLASS B NAC CIRCUITS. OPERATES 2-WIRE HORN/STR	725.00
AX-AL802ULADA	AL802ULADA	NAC POWER EXTENDER - 24VDC OR 12VDC @ 8 AMP. TWO (2) CLASS A OR FOUR (4) CLASS B NAC CIRCUITS. OPERATES 2-WIRE HORN/STR	725.00
AX-AL802ULADAJ	AL802ULADAJ	SAME FEATURES AS AL802ULADA IN LARGER ENCLOSURE 18"H X 14.5"W X 4.625"D.	761.11
AX-AL842UL2ADA	AL842UL2ADA	NAC POWER EXTENDER - 24VDC OR 12VDC @ 8 AMP. FOUR (4) CLASS A OR FOUR (4) CLASS B NAC CIRCUITS. OPERATES 2-WIRE HORN/ST	891.67
AX-AL842ULADA	AL842ULADA	NAC POWER EXTENDER - 24VDC OR 12VDC @ 8 AMP. FOUR (4) CLASS A OR FOUR (4) CLASS B NAC CIRCUITS. OPERATES 2-WIRE HORN/ST	891.67
AX-ALSD1	ALSD1	6VDC TO 12VDC OPERATION. TWO CHANNEL (YELP & STEADY), HIGH OUTPUT. CURRENT DRAW .5 TO 1.8 AMP (BASED ON SPEAKER RESISTA	35.56
AX-ALSD2	ALSD2	6VDC TO 12VDC OPERATION. TWO CHANNEL (YELP & STEADY). CURRENT DRAW .3 TO 1.22 AMP (BASED ON SPEAKER RESISTANCE AND SUPP	25.30
AX-ALTV1224C	ALTV1224C	EIGHT (8) FUSE PROTECTED OUTPUTS @ 24VAC 3.5 AMP PLUS EIGHT (8) FUSE PROTECTED OUTPUTS @ 12VDC 3.5 AMP, 7 AMP TOTAL CUR	346.32

AX-ALTV1224DC	ALTV1224DC	EIGHT (8) FUSE PROTECTED OUTPUTS, 12VDC OR 24VDC @ 4 AMP, 115VAC INPUT. GREY ENCLOSURE 15.5"H X 12"W X 4.5"D.	297.26
AX-ALTV1224DC1	ALTV1224DC1	SIXTEEN (16) FUSE PROTECTED OUTPUTS, 12VDC OR 24VDC @ 4 AMP, 115VAC INPUT. GREY ENCLOSURE 15.5"H X 12"W X 4.5"D.	323.23
AX-ALTV1224DC2	ALTV1224DC2	SIXTEEN (16) FUSE PROTECTED OUTPUTS, 12VDC OR 24VDC @ 6 AMP. 115VAC INPUT. GREY ENCLOSURE 15.5"H X 12"W X 4.5"D.	340.55
AX-ALTV2416	ALTV2416	SIXTEEN (16) FUSE PROTECTED OUTPUTS. 24VAC @ 8 AMP (200VA) OR 28VAC @ 7 AMP (200VA), 115VAC INPUT. GREY ENCLOSURE 8.5"H	256.85
AX-ALTV2416300UCBM	ALTV2416300UCBM	ALTV2416300ULCBM- SIXTEEN (16) PTC PROTECTED CLASS 2 RATED POWER LIMITED OUTPUTS. 24VAC @ 12.5 AMP (300VA) OR 28VAC @ 1	323.23
AX-ALTV2416300UL	ALTV2416300UL	SIXTEEN (16) FUSE PROTECTED OUTPUTS. 24VAC @ 12.5 AMP (300VA) OR 28VAC @ 10 AMP (280VA), 115VAC INPUT. GREY ENCLOSURE 1	340.55
AX-ALTV2416300ULCB	ALTV2416300ULCB	SIXTEEN (16) PTC PROTECTED CLASS 2 RATED POWER LIMITED OUTPUTS. 24VAC @ 12.5 AMP (300VA) OR 28VAC @ 10 AMP (280VA), 115	340.55
AX-ALTV2416300ULM	ALTV2416300ULM	SIXTEEN (16) FUSE PROTECTED OUTPUTS. 24VAC @ 12.5 AMP (300VA) OR 28VAC @ 10 AMP (280VA), 115VAC INPUT. GREY ENCLOSURE 8	323.23
AX-ALTV2416350	ALTV2416350	SIXTEEN (16) FUSE PROTECTED OUTPUTS. 24VAC @ 14 AMP (336VA) OR 28VAC @ 12.5 AMP (350VA), 115VAC INPUT. GREY ENCLOSURE 1	340.55
AX-ALTV2416350CB	ALTV2416350CB	SIXTEEN (16) PTC PROTECTED OUTPUTS. 24VAC @ 14 AMP (336VA) OR 28VAC @ 12.5 AMP (350VA), 115VAC INPUT. GREY ENCLOSURE 13	340.55
AX-ALTV2416600	ALTV2416600	SIXTEEN (16) FUSE PROTECTED OUTPUTS. 24VAC @ 28 AMP (675VA) OR 28VAC @ 25 AMP (700VA), 115VAC INPUT. GREY ENCLOSURE 13.	450.22
AX-ALTV2416600CB	ALTV2416600CB	SIXTEEN (16) PTC PROTECTED OUTPUTS. 24VAC @ 28 AMP (675VA) OR 28VAC @ 25 AMP (700VA), 115VAC INPUT. GREY ENCLOSURE 13.5	450.22
AX-ALTV2416600UL	ALTV2416600UL	SIXTEEN (16) FUSE PROTECTED OUTPUTS. 24VAC @ 25 AMP (600VA) OR 28VAC @ 20 AMP (560VA), 115VAC INPUT. GREY ENCLOSURE 13.	450.22
AX-ALTV2416600ULCB	ALTV2416600ULCB	SIXTEEN (16) PTC PROTECTED CLASS 2 RATED POWER LIMITED OUTPUTS. 24VAC @ 25 AMP (600VA) OR 28VAC @ 20 AMP (560VA), 115VA	450.22
AX-ALTV2416CB	ALTV2416CB	SIXTEEN (16) PTC PROTECTED OUTPUTS. 24VAC @ 8 AMP (200VA) OR 28VAC @ 7 AMP (200VA), 115VAC INPUT. GREY ENCLOSURE 8.5"H	256.85
AX-ALTV2416CBXX	ALTV2416CBXX	SIXTEEN (16) PTC PROTECTED OUTPUTS. 24VAC @ 8 AMP (200VA) OR 28VAC @ 7 AMP (200VA), 115VAC INPUT. GREY ENCLOSURE 15.5"H	277.06
AX-ALTV2416ULCBI	ALTV2416ULCBI	SIXTEEN (16) INDIVIDUALLY ELECTRONICALLY ISOLATED PTC PROTECTED CLASS 2 RATED POWER LIMITED OUTPUTS RATED @ 1.6 AMP EAC	479.08

AX-ALTV2416ULCBX	ALTV2416ULCBX	SIXTEEN (16) PTC PROTECTED CLASS 2 RATED POWER LIMITED OUTPUTS. 24VAC @ 7 AMP (170VA) OR 28VAC @ 6 AMP (170VA), 115VAC	262.63
AX-ALTV2416ULI	ALTV2416ULI	SIXTEEN (16) INDIVIDUALLY ELECTRONICALLY ISOLATED FUSE PROTECTED CLASS 2 RATED POWER LIMITED OUTPUTS RATED @ 1.6 AMP EA	479.08
AX-ALTV2416ULX	ALTV2416ULX	SIXTEEN (16) FUSE PROTECTED OUTPUTS. 24VAC @ 7 AMP (170VA) OR 28VAC @ 6 AMP (170VA), 115VAC INPUT. GREY ENCLOSURE 13.5"	262.63
AX-ALTV2432300UL	ALTV2432300UL	THIRTY-TWO (32) FUSE PROTECTED OUTPUTS. 24VAC @ 12.5 AMP (300VA) OR 28VAC @ 10 AMP (280VA), 115VAC INPUT. GREY ENCLOSUR	418.47
AX-ALTV2432300ULCB	ALTV2432300ULCB	THIRTY-TWO (32) PTC PROTECTED CLASS 2 RATED POWER LIMITED OUTPUTS. 24VAC @ 12.5 AMP (300VA) OR 28VAC @ 10 AMP (280VA),	418.47
AX-ALTV2432350	ALTV2432350	THIRTY-TWO (32) FUSE PROTECTED OUTPUTS. 24VAC @ 14 AMP (336VA) OR 28VAC @ 12.5 AMP (300VA), 115VAC INPUT. GREY ENCLOSUR	418.47
AX-ALTV2432350CB	ALTV2432350CB	THIRTY-TWO (32) PTC PROTECTED OUTPUTS. 24VAC @ 14 AMP (336VA) OR 28VAC @ 12.5 AMP (300VA), 115VAC INPUT. GREY ENCLOSURE	418.47
AX-ALTV2432600	ALTV2432600	THIRTY-TWO (32) FUSE PROTECTED OUTPUTS. 24VAC @ 28 AMP (675VA) OR 28VAC @ 25 AMP (700VA), 115VAC INPUT. GREY ENCLOSURE	481.96
AX-ALTV2432600CB	ALTV2432600CB	THIRTY-TWO (32) PTC PROTECTED OUTPUTS. 24VAC @ 28 AMP (675VA) OR 28VAC @ 25 AMP (700VA), 115VAC INPUT. GREY ENCLOSURE 1	481.96
AX-ALTV2432600UL	ALTV2432600UL	THIRTY-TWO (32) FUSE PROTECTED OUTPUTS, 24VAC @ 25 AMP (600VA) OR 28VAC @ 20 AMP (560VA), 115VAC INPUT. GREY ENCLOSURE	481.96
AX-ALTV2432600ULCB	ALTV2432600ULCB	THIRTY-TWO (32) PTC PROTECTED CLASS 2 RATED POWER LIMITED OUTPUTS. 24VAC @ 25 AMP (600VA) OR 28VAC @ 20 AMP (560VA), 11	481.96
AX-ALTV244	ALTV244	FOUR (4) FUSE PROTECTED OUTPUTS. 24VAC @ 4 AMP (100VA) OR 28VAC @ 3.5 AMP (100VA), 115VAC INPUT. GREY ENCLOSURE 8.5"H X	124.44
AX-ALTV244175	ALTV244175	FOUR (4) FUSE PROTECTED OUTPUTS. 24VAC @ 7.25 AMP (175VA) OR 28VAC @ 6.25 AMP (175VA), 115VAC INPUT. GREY ENCLOSURE 8.5	164.50
AX-ALTV244175CB	ALTV244175CB	FOUR (4) PTC PROTECTED OUTPUTS. 24VAC @ 7.25 AMP (175VA) OR 28VAC @ 6.25 AMP (175VA), 115VAC INPUT. GREY ENCLOSURE 8.5"	164.50
AX-ALTV244175UL	ALTV244175UL	FOUR (4) FUSE PROTECTED OUTPUTS. 24VAC @ 7 AMP (175VA) OR 28VAC @ 6.25 AMP (175VA), 115VAC INPUT. GREY ENCLOSURE 12.25"	202.02
AX-ALTV244175ULCB	ALTV244175ULCB	FOUR (4) PTC PROTECTED CLASS 2 RATED POWER LIMITED OUTPUTS. 24VAC @ 7 AMP (175VA) OR 28VAC @ 6.25 AMP (175VA), 115VAC I	202.02
AX-ALTV244300	ALTV244300	FOUR (4) FUSE PROTECTED OUTPUTS. 24VAC @ 14 AMP (336VA) OR 28VAC @ 12.5 AMP (350VA), 115VAC INPUT. GREY ENCLOSURE 8.5"H	282.83

AX-ALTV244300CB	ALTV244300CB	FOUR (4) PTC PROTECTED OUTPUTS. 24VAC @ 14 AMP (336VA) OR 28VAC @ 12.5 AMP (350VA), 115VAC INPUT. GREY ENCLOSURE 8.5"H	282.83
AX-ALTV244CB	ALTV244CB	FOUR (4) PTC PROTECTED OUTPUTS. 24VAC @ 4 AMP (100VA) OR 28VAC @ 3.5 AMP (100VA), 115VAC INPUT. GREY ENCLOSURE 8.5"H X	124.44
AX-ALTV244UL	ALTV244UL	FOUR (4) FUSE PROTECTED OUTPUTS. 24VAC @ 3.5 AMP (85VA) OR 28VAC @ 3 AMP (85VA), 115VAC INPUT. GREY ENCLOSURE 8.5"H X 7	127.41
AX-ALTV244ULCB	ALTV244ULCB	FOUR (4) PTC PROTECTED CLASS 2 RATED POWER LIMITED OUTPUTS. 24VAC @ 3.5 AMP (85VA) OR 28VAC @ 3 AMP (85VA), 115VAC INPU	127.41
AX-ALTV248	ALTV248	EIGHT (8) FUSE PROTECTED OUTPUTS. 24VAC @ 4 AMP (100VA) OR 28VAC @ 3.5 AMP (100VA), 115VAC INPUT. GREY ENCLOSURE 8.5"H	155.84
AX-ALTV248175UL	ALTV248175UL	EIGHT (8) FUSE PROTECTED OUTPUTS. 24VAC @ 7 AMP (175VA) OR 28VAC @ 6.25 AMP (175VA), 115VAC INPUT. GREY ENCLOSURE 12.25	219.34
AX-ALTV248175ULCB	ALTV248175ULCB	EIGHT (8) PTC PROTECTED CLASS 2 RATED POWER LIMITED OUTPUTS. 24VAC @ 7 AMP (175VA) OR 28VAC @ 6.25 AMP (175VA), 115VAC	219.34
AX-ALTV248300	ALTV248300	EIGHT (8) FUSE PROTECTED OUTPUTS. 24VAC @ 14 AMP (336VA) OR 28VAC @ 12.5 AMP (350VA), 115VAC INPUT. GREY ENCLOSURE 8.5"	314.57
AX-ALTV248300CB	ALTV248300CB	EIGHT (8) PTC PROTECTED OUTPUTS. 24VAC @ 14 AMP (336VA) OR 28VAC @ 12.5 AMP (350VA), 115VAC INPUT. GREY ENCLOSURE 8.5"H	314.57
AX-ALTV248300UL	ALTV248300UL	EIGHT (8) FUSE PROTECTED OUTPUTS. 24VAC @ 12.5 AMP (300VA) OR 28VAC @ 10 AMP (280VA), 115VAC INPUT. GREY ENCLOSURE 13.5	314.57
AX-ALTV248300ULCB	ALTV248300ULCB	EIGHT (8) PTC PROTECTED CLASS 2 RATED POWER LIMITED OUTPUTS. 24VAC @ 12.5 AMP (300VA) OR 28VAC @ 10 AMP (280VA), 115VAC	314.57
AX-ALTV248300ULCBM	ALTV248300ULCBM	EIGHT (8) PTC PROTECTED CLASS 2 RATED POWER LIMITED OUTPUTS. 24VAC @ 12.5 AMP (300VA) OR 28VAC @ 10 AMP (280VA), 115VAC	300.14
AX-ALTV248300ULM	ALTV248300ULM	EIGHT (8) FUSE PROTECTED OUTPUTS. 24VAC @ 12.5 AMP (300VA) OR 28VAC @ 10 AMP (280VA), 115VAC INPUT. GREY ENCLOSURE 8.5"	300.14
AX-ALTV248600	ALTV248600	EIGHT (8) FUSE PROTECTED OUTPUTS. 24VAC @ 28 AMP (675VA) OR 28VAC @ 25 AMP (700VA), 115VAC INPUT. GREY ENCLOSURE 13.5"H	427.13
AX-ALTV248600CB	ALTV248600CB	EIGHT (8) PTC PROTECTED OUTPUTS. 24VAC @ 28 AMP (675VA) OR 28VAC @ 25 AMP (700VA), 115VAC INPUT. GREY ENCLOSURE 13.5"H	427.13
AX-ALTV248600UL	ALTV248600UL	EIGHT (8) FUSE PROTECTED OUTPUTS. 24VAC @ 25 AMP (600VA) OR 28VAC @ 20 AMP (560VA), 115VAC INPUT. GREY ENCLOSURE 13.5"H	427.13
AX-ALTV248600ULCB	ALTV248600ULCB	EIGHT (8) PTC PROTECTED CLASS 2 RATED POWER LIMITED OUTPUTS. 24VAC @ 25 AMP (600VA) OR 28VAC @ 20 AMP (560VA), 115VAC I	427.13

AX-ALTV248CB	ALTV248CB	EIGHT (8) PTC PROTECTED OUTPUTS. 24VAC @ 4 AMP (100VA) OR 28VAC @ 3.5 AMP (100VA), 115VAC INPUT. GREY ENCLOSURE 8.5"H X	155.84
AX-ALTV248UL	ALTV248UL	EIGHT (8) FUSE PROTECTED OUTPUTS. 24VAC @ 3.5 AMP (85VA) OR 28VAC @ 3 AMP (85VA,) 115VAC INPUT. GREY ENCLOSURE 8.5"H X	158.73
AX-ALTV248ULCB	ALTV248ULCB	EIGHT (8) PTC PROTECTED CLASS 2 RATED POWER LIMITED OUTPUTS. 24VAC @ 3.5 AMP (85VA) OR 28VAC @ 3 AMP (85VA), 115VAC INP	158.73
AX-ALTV248ULCBHI	ALTV248ULCBHI	EIGHT (8) INDIVIDUALLY ELECTRONICALLY ISOLATED PTC PROTECTED CLASS 2 RATED POWER LIMITED OUTPUTS RATED @ 1.6 AMP EACH.	329.00
AX-ALTV248ULCBMI	ALTV248ULCBMI	EIGHT (8) INDIVIDUALLY ELECTRONICALLY ISOLATED PTC PROTECTED CLASS 2 RATED POWER LIMITED OUTPUTS RATED @ 1.6 AMP EACH.	317.46
AX-ALTV248ULHI	ALTV248ULHI	EIGHT (8) INDIVIDUALLY ELECTRONICALLY ISOLATED FUSE PROTECTED CLASS 2 RATED POWER LIMITED OUTPUTS RATED @ 1.6 AMP EACH.	329.00
AX-ALTV248ULMI	ALTV248ULMI	EIGHT (8) INDIVIDUALLY ELECTRONICALLY ISOLATED FUSE PROTECTED CLASS 2 RATED POWER LIMITED OUTPUTS RATED @ 1.6 AMP EACH.	317.46
AX-ALTV615DC1016	ALTV615DC1016	SIXTEEN (16) FUSE PROTECTED OUTPUTS, 6-15VDC @ 10 AMP, 115VAC INPUT. GREY ENCLOSURE 13.5"H X 13"W X 3.25"D.	386.72
AX-ALTV615DC1016CB	ALTV615DC1016CB	SIXTEEN (16) PTC OUTPUTS, 6-15VDC @ 10 AMP. 115VAC INPUT. GREY ENCLOSURE 13.5"H X 13"W X 3.25"D.	386.72
AX-ALTV615DC416UBM	ALTV615DC416UBM	SIXTEEN (16) PTC PROTECTED CLASS 2 RATED POWER LIMITED OUTPUTS. 6-15VDC @ 4 AMP, 115VAC INPUT. GREY ENCLOSURE 8.5"H X 7	265.51
AX-ALTV615DC416UCB	ALTV615DC416UCB	SIXTEEN (16) PTC PROTECTED CLASS 2 RATED POWER LIMITED OUTPUTS. 6-15VDC @ 4 AMP, 115VAC INPUT. GREY ENCLOSURE 13.5"H X	311.69
AX-ALTV615DC416UL	ALTV615DC416UL	SIXTEEN (16) FUSE PROTECTED CLASS 2 RATED POWER LIMITED OUTPUTS, 6-15VDC @ 4 AMP, 115VAC INPUT. GREY ENCLOSURE 13.5"H X	311.69
AX-ALTV615DC44UCBM	ALTV615DC44UCBM	FOUR (4) PTC PROTECTED CLASS 2 RATED POWER LIMITED OUTPUTS. 6-15VDC @ 4 AMP, 115VAC INPUT. GREY ENCLOSURE 8.5"H X 7.5"W	199.13
AX-ALTV615DC44ULM	ALTV615DC44ULM	FOUR (4) FUSE PROTECTED CLASS 2 RATED POWER LIMITED OUTPUTS, 6-15VDC @ 4 AMP, 115VAC INPUT. GREY ENCLOSURE 8.5"H X 7.5"	199.13
AX-ALTV615DC48UCBM	ALTV615DC48UCBM	EIGHT (8) PTC PROTECTED CLASS 2 RATED POWER LIMITED OUTPUTS. 6-15VDC @ 4 AMP, 115VAC INPUT. GREY ENCLOSURE 8.5"H X 7.5"	230.88
AX-ALTV615DC48ULM	ALTV615DC48ULM	EIGHT (8) FUSE PROTECTED CLASS 2 RATED POWER LIMITED OUTPUTS, 6-15VDC @ 4 AMP, 115VAC INPUT. GREY ENCLOSURE 8.5"H X 7.5	230.88
AX-ALTV615DC4UL	ALTV615DC4UL	FOUR (4) FUSE PROTECTED CLASS 2 RATED POWER LIMITED OUTPUTS, 6-12VDC @ 2.5 AMP OR 12-15VDC @ 2 AMP, 24VAC 40VA OR 24VAC	155.84

AX-ALTV615DC616UCB	ALTV615DC616UCB	SIXTEEN (16) PTC PROTECTED CLASS 2 RATED POWER LIMITED OUTPUTS. 6-15VDC @ 6 AMP, 115VAC INPUT. GREY ENCLOSURE 13.5"H X	340.55
AX-ALTV615DC616UL	ALTV615DC616UL	SIXTEEN (16) FUSE PROTECTED OUTPUTS, 6-15 VDC @ 6 AMP, 115VAC INPUT. GREY ENCLOSURE 13.5"H X 13"W X 3.25"D. UL LISTED (340.55
AX-ALTV615DC8UL	ALTV615DC8UL	EIGHT (8) FUSE PROTECTED CLASS 2 RATED POWER LIMITED OUTPUTS, 6-15VDC @ 4 AMP, 115VAC INPUT. GREY ENCLOSURE 13.5"H X 13	279.94
AX-ALTV615DC8ULCB	ALTV615DC8ULCB	EIGHT (8) PTC PROTECTED CLASS 2 RATED POWER LIMITED OUTPUTS. 6-15VDC @ 4 AMP, 115VAC INPUT. GREY ENCLOSURE 13.5"H X 13"	279.94
AX-AT4	AT4	FOUR CHANNEL ANNUAL EVENT TIMER - 12 TO 24 VOLT AC OR DC OPERATION. 365 DAY/24 HR. TIMER. PROGRAMMABLE FEATURES PER CHA	386.72
AX-AT4B	AT4B	FOUR CHANNEL ANNUAL EVENT TIMER - 12 TO 24 VOLT AC OR DC OPERATION. 365 DAY/24 HR. TIMER. PROGRAMMABLE FEATURES PER CHA	354.98
AX-BC100	BC100	GREY ENCLOSURE 8.5"H X 7.5"W X 3.5"D, 19 GAUGE STEEL. FITS EITHER TWO (2) 12VDC/4AH BATTERIES OR ONE (1) 12VDC/7AH BATT	62.22
AX-BC1240	BC1240	GREY ENCLOSURE 9.5"H X 9.5"W X 7.5"D, 19 GAUGE STEEL, INCLUDES CAM LOCK. FITS ONE (1) 12VDC/40AH BATTERY.	133.33
AX-BC200	BC200	GREY ENCLOSURE 12.25"H X 7.75"W X 4.5"D, 19 GAUGE STEEL, INCLUDES CAM LOCK. FITS UP TO TWO (2) 12VDC/7AH BATTERIES.	74.07
AX-BC300	BC300	GREY ENCLOSURE 13.5"H X 13"W X 3.25"D, 19 GAUGE STEEL, INCLUDES CAM LOCK. FITS UP TO TWO (2) 12VDC/7AH BATTERIES.	100.74
AX-BC300R	BC300R	RED ENCLOSURE 13.5"H X 13"W X 3.25"D, 19 GAUGE STEEL, INCLUDES CAM LOCK. FITS UP TO TWO (2) 12VDC/7AH BATTERIES.	100.74
AX-BC400	BC400	GREY ENCLOSURE 15.5"H X 12"W X 4.5"D, 19 GAUGE STEEL, INCLUDES CAM LOCK. FITS UP TO TWO (2) 12VDC/12AH BATTERIES.	139.26
AX-BC400R	BC400R	RED ENCLOSURE 15.5"H X 12"W X 4.5"D, 19 GAUGE STEEL, INCLUDES CAM LOCK. FITS UP TO TWO (2) 12VDC/12AH BATTERIES.	139.26
AX-BC400SG	BC400SG	GREY ENCLOSURE 15.5"H X 12"W X 4.5"D, 19 GAUGE STEEL, INCLUDES BATTERY SHELF (BCS4G) AND CAM LOCK. FITS UP TO TWO (2) 1	181.82
AX-BC400SR	BC400SR	RED ENCLOSURE 15.5"H X 12"W X 4.5"D, 19 GAUGE STEEL, INCLUDES BATTERY SHELF (BCS4R) AND CAM LOCK. FITS UP TO TWO (2) 12	181.82
AX-BC600	BC600	RED ENCLOSURE 18"H X 14.5"W X 4.5"D, 19 GAUGE STEEL, INCLUDES CAM LOCK. FITS UP TO TWO (2) 12VDC/12AH BATTERIES.	170.27
AX-BC800	BC800	EXPANDABLE ACCESS/FIRE POWER SYSTEM GREY ENCLOSURE 26"H X 19"W X 6.25"D, 16 GAUGE STEEL, INCLUDES CAM LOCK. ENCLOSURE A	502.16
AX-BCS4G	BCS4G	GREY BATTERY SHELF FOR BC400.	56.30
AX-BCS4R	BCS4R	RED BATTERY SHELF FOR BC400R.	56.30

AX-BL2	BL2	RED AND BLACK 8" BATTERY LEADS	1.90
AX-BL3	BL3	RED AND BLACK 18" BATTERY LEADS	3.76
AX-BL4	BL4	YELLOW 8" BATTERY JUMPER LEAD	3.76
AX-BT1212	BT1212	12VDC/12AH, DIMENSIONS 3.5"H X 5.94"W X 3.75"D.	121.48
AX-BT124	BT124	12VDC/4AH, DIMENSIONS 4"H X 3.5"W X 2.76"D.	47.41
AX-BT1240	BT1240	12VDC/40AH, DIMENSIONS 6.73"H X 7.72"W X 6.5"D.	274.17
AX-BT126	BT126	12VDC/7AH, DIMENSIONS 3.66"H X 5.94"W X 2.56"D.	59.26
AX-CAB4	CAB4	GREY ENCLOSURE 5.63"H X 7"W X 4.5"D, 19 GAUGE STEEL. FITS ONE (1) 12VDC/12AH BATTERY.	88.89
AX-CAM1	CAM1	CAM LOCK W/MOUNTING HARDWARE	11.32
AX-CP1	CP1	CONVERSION PLATE FOR MOUNTING 2 PD8 OR 2 MOM5 BOARDS IN BC 400 ENCLOSURE	26.43
AX-D10	D10	DIN RAIL PRE-CUT TO 10" LENGTH FOR MOUNTING DIN RAIL PRODUCTS.	11.32
AX-DL1	DL1	DOOR CONTROL TIMER, 12 TO 24 VOLT AC OR DC OPERATION. USE WITH MAGNETIC LOCKS AND ELECTRIC STRIKES.	82.96
AX-DL3	DL3	DOOR CONTROL TIMER W/ SOUNDER, 12 TO 24 VOLT AC OR DC OPERATION. USE WITH MAGNETIC LOCKS AND ELECTRIC STRIKES.	106.67
AX-DP4	DP4	POWER DISTRIBUTION BOARD - FOUR (4) INDIVIDUALLY FUSE PROTECTED OUTPUTS. HANDLES UP TO 28VAC/VDC. INCLUDES SNAP TRACK A	85.93
AX-DPS1	DPS1	POWER SUPPLY/CHARGER - 6VDC OR 12VDC @ 1.2 AMP OR 24VDC @ 750MA OUTPUT. INCLUDES SNAP TRACK AND MOUNTING CLIPS.	53.33
AX-DPS3	DPS3	POWER SUPPLY/CHARGER - 6VDC, 12VDC OR 24VDC RATED @ 2.5 AMP OUTPUT. INCLUDES SNAP TRACK AND MOUNTING CLIPS.	97.78
AX-DPS5	DPS5	POWER SUPPLY/CHARGER - 6VDC, 12VDC OR 24VDC RATED @ 4 AMP OUTPUT. INCLUDES SNAP TRACK AND MOUNTING CLIPS.	130.37
AX-DPT724A	DPT724A	ANNUAL EVENT TIMER - 12 TO 24 VOLT AC OR DC OPERATION. 365 DAY/24 HR. TIMER. PROGRAMMABLE FEATURES: 50 INDIVIDUAL DAILY	196.25
AX-DTMR1	DTMR1	MULTI-FUNCTION TIMER, 12VDC OR 24VDC OPERATION. 1 SEC. TO 60 MIN. ADJUSTABLE TIMING RANGE. ONE SECOND MOMENTARY RELAY A	82.96
AX-DVT1	DVT1	DUAL VOLTAGE 24VAC OR 28VAC, 80VA TOTAL. 120VAC INPUT, ENCLOSED IN HIGH IMPACT PLASTIC CASE.	106.67
AX-FUSE1	FUSE1	3.5 AMP GLASS FUSE. USED IN CCTV POWER SUPPLIES. PACKAGE OF 100	88.89
AX-FUSE2	FUSE2	5 AMP GLASS FUSE. USED IN CCTV POWER SUPPLIES. PACKAGE OF 100	88.89
AX-GL1	GL1	GREEN 8" GROUND LEAD	1.90
AX-HUBSAT42S	HUBSAT42S	FOUR (4) CHANNEL PASSIVE UTP TRANSCEIVER HUB WITH INTEGRAL CAMERA POWER, 24VAC AND/OR 28VAC @ 4 AMP, 115VAC INPUT 50/60	554.11
AX-HUBSAT43S	HUBSAT43S	FOUR (4) CHANNEL PASSIVE UTP TRANSCEIVER HUB WITH INTEGRAL CAMERA POWER, 24VAC AND/OR 28VAC @ 4 AMP, 115VAC INPUT 50/60	594.44

AX-HUBSAT4S	HUBSAT4S	FOUR (4) CHANNEL PASSIVE UTP TRANSCEIVER HUB WITH INTEGRAL CAMERA POWER, 24VAC AND/OR 28VAC @ 4 AMP, 115VAC INPUT 50/60	418.47
AX-HUBWAY2	HUBWAY2	VIDEO/DATA/POWER OVER CAT5 (UTP)- EIGHT (8) SELECTABLE FUSE PROTECTED OUTPUTS. 24VAC OR 28VAC @ 8 AMP TOTAL CURRENT, 11	788.89
AX-HUBWAY22	HUBWAY22	SAME AS HUBWAY2 WITH EIGHT (8) 24VAC/28VAC VIDEO BALUN/COMBINERS INCLUDED.	1050.00
AX-HUBWAY22I	HUBWAY22I	SAME AS HUBWAY2I WITH EIGHT (8) 24VAC/28VAC VIDEO BALUN/COMBINERS INCLUDED. 2U RACK MOUNT CHASSIS FOR USE IN STANDARD E	1152.78
AX-HUBWAY23	HUBWAY23	SAME AS HUBWAY2 WITH EIGHT (8) 12VDC VIDEO BALUN/COMBINERS INCLUDED.	1172.22
AX-HUBWAY23I	HUBWAY23I	SAME AS HUBWAY2I WITH EIGHT (8) 12VDC VIDEO BALUN/COMBINERS INCLUDED. 2U RACK MOUNT CHASSIS FOR USE IN STANDARD EIA 19"	1275.00
AX-HUBWAY2I	HUBWAY2I	VIDEO/DATA/POWER OVER CAT5 (UTP)- EIGHT (8) ELECTRONICALLY ISOLATED FUSE PROTECTED OUTPUTS. 24VAC @ 8 AMP TOTAL CURRENT	891.67
AX-HUBWAY82S	HUBWAY82S	EIGHT (8) CHANNEL PASSIVE UTP TRANSCEIVER HUB WITH INTEGRAL CAMERA POWER, 24VAC AND/OR 28VAC @ 5.5 AMP (150VA), 115/230	1080.56
AX-HUBWAY83S	HUBWAY83S	EIGHT (8) CHANNEL PASSIVE UTP TRANSCEIVER HUB WITH INTEGRAL CAMERA POWER, 24VAC AND/OR 28VAC @ 5.5 AMP (150VA), 115/230	1202.78
AX-HUBWAY8S	HUBWAY8S	EIGHT (8) CHANNEL PASSIVE UTP TRANSCEIVER HUB WITH INTEGRAL CAMERA POWER, 24VAC AND/OR 28VAC @ 5.5 AMP (150VA), 115/230	819.44
AX-HUBWAYA	HUBWAYA	VIDEO/DATA/POWER OVER CAT5 (UTP)- 24VAC OR 28VAC VIDEO BALUN/COMBINER.	47.41
AX-HUBWAYD	HUBWAYD	VIDEO/DATA/POWER OVER CAT5 (UTP)- 12VDC VIDEO BALUN/COMBINER.	71.11
AX-HUBWAYLD82S	HUBWAYLD82S	EIGHT (8) CHANNEL ACTIVE UTP TRANSCEIVER HUB WITH INTEGRAL CAMERA POWER, 24VAC AND/OR 28VAC @ 5.5 AMP (150VA), 115/230V	1750.68
AX-HUBWAYLD83S	HUBWAYLD83S	EIGHT (8) CHANNEL ACTIVE UTP TRANSCEIVER HUB WITH INTEGRAL CAMERA POWER, 24VAC AND/OR 28VAC @ 5.5 AMP (150VA), 115/230V	1867.21
AX-HUBWAYLD8S	HUBWAYLD8S	EIGHT (8) CHANNEL ACTIVE UTP TRANSCEIVER HUB WITH INTEGRAL CAMERA POWER, 24VAC AND/OR 28VAC @ 5.5 AMP (150VA), 115/230V	1498.64
AX-HUBWAYLDH8S	HUBWAYLDH8S	EIGHT (8) CHANNEL ACTIVE UTP TRANSCEIVER HUB, 115/230VAC INPUT 50/60HZ. VIDEO/DATA UP TO 3000 FT. ALL CONNECTIONS ON RE	1291.67
AX-LB2032	LB2032	3V LITHIUM BATTERY FOR AT4, PT2724, PT724A AND PT724AE.	7.56
AX-LC1	LC1	2 CONDUCTOR 6 FT LINE CORD	4.53
AX-LC2	LC2	6FT. 3-WIRE LINE CORD	9.42
AX-LPD	LPD	12/24 VDC LOW POWER DISCONNECT MODULE DISCONNECTS AT 10.5 / 21 VDC	32.59
AX-LPS3	LPS3	12VDC OR 24VDC @ 2.5 AMP, OVER VOLTAGE PROTECTION.	103.70

AX-LPS3AC	LPS3AC	12VDC OR 24VDC @ 2.5 AMP, OVER VOLTAGE PROTECTION AND AC MONITORING.	136.30
AX-LPS3C12X	LPS3C12X	12VDC @ 2.5 AMP, OVER VOLTAGE PROTECTION, GREY ENCLOSURE 13.5"H X 13"W X 3.25"D.	294.37
AX-LPS3C24X	LPS3C24X	24VDC @ 2.5 AMP, OVER VOLTAGE PROTECTION, GREY ENCLOSURE 13.5"H X 13"W X 3.25"D.	294.37
AX-LPS3WP12	LPS3WP12	12VDC @ 2.5 AMP, OVER VOLTAGE PROTECTION, NEMA4/IP65 OUTDOOR RATED ENCLOSURE 12"H X 8"W X 6"D.	415.58
AX-LPS3WP24	LPS3WP24	24VDC @ 2.5 AMP, OVER VOLTAGE PROTECTION, NEMA4/IP65 OUTDOOR RATED ENCLOSURE 12"H X 8"W X 6"D.	415.58
AX-LPS5C12X	LPS5C12X	12VDC @ 3.5 AMP, 115VAC INPUT, AC AND BATTERY MONITORING, GREY ENCLOSURE 13.5"H X 13"W X 3.25"D.	337.66
AX-LPS5C24X	LPS5C24X	24VDC @ 3.5 AMP, 115VAC INPUT, AC AND BATTERY MONITORING, GREY ENCLOSURE 13.5"H X 13"W X 3.25"D.	337.66
AX-MAXIM11	MAXIM11	ACCESS POWER CONTROLLER PROVIDING A TOTAL OF SIXTEEN (16) FUSE PROTECTED FAIL-SAFE AND/OR FAIL-SECURE POWER OUTPUTS OR	1041.67
AX-MAXIM11D	MAXIM11D	ACCESS POWER CONTROLLER PROVIDING A TOTAL OF SIXTEEN (16) PTC PROTECTED FAIL-SAFE AND/OR FAIL-SECURE POWER OUTPUTS, FIR	1041.67
AX-MAXIM11E	MAXIM11E	UNIT INCLUDES TWO (2) POWER SUPPLY/CHARGERS WHICH ARE 12VDC @ 4 AMP OR 24VDC @ 3 AMP, 115VAC INPUT, AC AND BATTERY MONI	813.89
AX-MAXIM13E	MAXIM13E	UNIT INCLUDES ONE (1) POWER SUPPLY/CHARGER WHICH IS 12VDC @ 4 AMP OR 24VDC @ 3 AMP AND ONE (1) POWER SUPPLY/CHARGER WHI	980.56
AX-MAXIM1R	MAXIM1R	ACCESS POWER CONTROLLER PROVIDING A TOTAL OF SIXTEEN (16) FUSE PROTECTED FAIL-SAFE AND/OR FAIL-SECURE OUTPUTS, FIRE ALA	777.78
AX-MAXIM1RD	MAXIM1RD	ACCESS POWER CONTROLLER PROVIDING A TOTAL OF SIXTEEN (16) PTC PROTECTED FAIL-SAFE AND/OR FAIL-SECURE OUTPUTS, FIRE ALAR	777.78
AX-MAXIM1RH	MAXIM1RH	ACCESS POWER CONTROLLER PROVIDING A TOTAL OF EIGHT (8) FUSE PROTECTED FAIL-SAFE AND/OR FAIL-SECURE OUTPUTS, FIRE ALARM	688.89
AX-MAXIM1RHD	MAXIM1RHD	ACCESS POWER CONTROLLER PROVIDING A TOTAL OF EIGHT (8) PTC PROTECTED FAIL-SAFE AND/OR FAIL-SECURE OUTPUTS, FIRE ALARM I	688.89
AX-MAXIM3	MAXIM3	ACCESS POWER CONTROLLER PROVIDING A TOTAL OF SIXTEEN (16) FUSE PROTECTED FAIL-SAFE AND/OR FAIL-SECURE NON-POWER LIMITED	927.78
AX-MAXIM33	MAXIM33	ACCESS POWER CONTROLLER PROVIDING A TOTAL OF SIXTEEN (16) FUSE PROTECTED FAIL-SAFE AND/OR FAIL-SECURE NON-POWER LIMITED	1372.22
AX-MAXIM33D	MAXIM33D	ACCESS POWER CONTROLLER PROVIDING A TOTAL OF SIXTEEN (16) PTC PROTECTED FAIL-SAFE AND/OR FAIL-SECURE POWER OUTPUTS, FIR	1372.22
AX-MAXIM33E	MAXIM33E	UNIT INCLUDES TWO (2) POWER SUPPLY/CHARGERS WHICH ARE 12VDC OR 24VDC @ 6 AMP, 115VAC INPUT, AC AND BATTERY MONITORING.	1144.44

AX-MAXIM33R	MAXIM33R	ACCESS POWER CONTROLLER PROVIDING A TOTAL OF SIXTEEN (16) FUSE PROTECTED FAIL-SAFE AND/OR FAIL-SECURE OUTPUTS, FIRE ALA	1252.78
AX-MAXIM33RD	MAXIM33RD	ACCESS POWER CONTROLLER PROVIDING A TOTAL OF SIXTEEN (16) PTC PROTECTED FAIL-SAFE AND/OR FAIL-SECURE OUTPUTS, FIRE ALAR	1252.78
AX-MAXIM35E	MAXIM35E	UNIT INCLUDES ONE (1) POWER SUPPLY/CHARGER WHICH IS 12VDC OR 24VDC @ 6 AMP AND ONE (1) POWER SUPPLY/CHARGER WHICH IS 12	1205.56
AX-MAXIM37E	MAXIM37E	UNIT INCLUDES ONE (1) POWER SUPPLY/CHARGER WHICH IS 12VDC OR 24VDC @ 6 AMP AND ONE (1) POWER SUPPLY/CHARGER WHICH IS 24	1263.89
AX-MAXIM3D	MAXIM3D	ACCESS POWER CONTROLLER PROVIDING A TOTAL OF SIXTEEN (16) PTC PROTECTED FAIL-SAFE AND/OR FAIL-SECURE POWER OUTPUTS, FIR	927.78
AX-MAXIM3R	MAXIM3R	ACCESS POWER CONTROLLER PROVIDING A TOTAL OF SIXTEEN (16) FUSE PROTECTED FAIL-SAFE AND/OR FAIL-SECURE OUTPUTS, FIRE ALA	838.89
AX-MAXIM3RD	MAXIM3RD	ACCESS POWER CONTROLLER PROVIDING A TOTAL OF SIXTEEN (16) PTC PROTECTED FAIL-SAFE AND/OR FAIL-SECURE OUTPUTS, FIRE ALAR	838.89
AX-MAXIM3RH	MAXIM3RH	ACCESS POWER CONTROLLER PROVIDING A TOTAL OF EIGHT (8) FUSE PROTECTED FAIL-SAFE AND/OR FAIL-SECURE OUTPUTS, FIRE ALARM	747.22
AX-MAXIM3RHD	MAXIM3RHD	ACCESS POWER CONTROLLER PROVIDING A TOTAL OF EIGHT (8) PTC PROTECTED FAIL-SAFE AND/OR FAIL-SECURE OUTPUTS, FIRE ALARM I	747.22
AX-MAXIM5	MAXIM5	ACCESS POWER CONTROLLER PROVIDING A TOTAL OF SIXTEEN (16) FUSE PROTECTED FAIL-SAFE AND/OR FAIL-SECURE NON-POWER LIMITED	986.11
AX-MAXIM55	MAXIM55	ACCESS POWER CONTROLLER PROVIDING A TOTAL OF SIXTEEN (16) FUSE PROTECTED FAIL-SAFE AND/OR FAIL-SECURE NON-POWER LIMITED	1439.02
AX-MAXIM55D	MAXIM55D	ACCESS POWER CONTROLLER PROVIDING A TOTAL OF SIXTEEN (16) PTC PROTECTED FAIL-SAFE AND/OR FAIL-SECURE NON-POWER LIMITED	1439.02
AX-MAXIM55E	MAXIM55E	UNIT INCLUDES TWO (2) POWER SUPPLY/CHARGERS WHICH ARE 12VDC @ 10 AMP, 115VAC INPUT, AC AND BATTERY MONITORING. SYSTEM C	1263.89
AX-MAXIM5D	MAXIM5D	ACCESS POWER CONTROLLER PROVIDING A TOTAL OF SIXTEEN (16) PTC PROTECTED FAIL-SAFE AND/OR FAIL-SECURE POWER OUTPUTS, FIR	986.11
AX-MAXIM7	MAXIM7	ACCESS POWER CONTROLLER PROVIDING A TOTAL OF SIXTEEN (16) FUSE PROTECTED FAIL-SAFE AND/OR FAIL-SECURE NON-POWER LIMITED	1044.44
AX-MAXIM75	MAXIM75	ACCESS POWER CONTROLLER PROVIDING A TOTAL OF SIXTEEN (16) FUSE PROTECTED FAIL-SAFE AND/OR FAIL-SECURE NON-POWER LIMITED	1495.93
AX-MAXIM75D	MAXIM75D	ACCESS POWER CONTROLLER PROVIDING A TOTAL OF SIXTEEN (16) PTC PROTECTED FAIL-SAFE AND/OR FAIL-SECURE NON-POWER LIMITED	1495.93

AX-MAXIM75E	MAXIM75E	UNIT INCLUDES ONE (1) POWER SUPPLY/CHARGER WHICH IS 12VDC @ 10 AMP AND ONE (1) POWER SUPPLY/CHARGER WHICH IS 24VDC @ 10	1322.22
AX-MAXIM77	MAXIM77	ACCESS POWER CONTROLLER PROVIDING A TOTAL OF SIXTEEN (16) FUSE PROTECTED FAIL-SAFE AND/OR FAIL-SECURE NON-POWER LIMITED	1555.56
AX-MAXIM77D	MAXIM77D	ACCESS POWER CONTROLLER PROVIDING A TOTAL OF SIXTEEN (16) PTC PROTECTED FAIL-SAFE AND/OR FAIL-SECURE NON-POWER LIMITED	1555.56
AX-MAXIM77E	MAXIM77E	UNIT INCLUDES TWO (2) POWER SUPPLY/CHARGERS WHICH ARE 24VDC @ 10 AMP, 115VAC INPUT, AC AND BATTERY MONITORING. SYSTEM C	1383.33
AX-MAXIM7D	MAXIM7D	ACCESS POWER CONTROLLER PROVIDING A TOTAL OF SIXTEEN (16) PTC PROTECTED FAIL-SAFE AND/OR FAIL-SECURE POWER OUTPUTS, FIR	1044.44
AX-MOM5	MOM5	UL RECOGNIZED MULTI-OUTPUT POWER DISTRIBUTION MODULE. FIVE (5) INDIVIDUALLY PTC PROTECTED CLASS 2 RATED POWER LIMITED O	155.84
AX-MOM5C	MOM5C	MULTI-OUTPUT POWER DISTRIBUTION MODULE. FIVE (5) INDIVIDUALLY PTC PROTECTED CLASS 2 RATED POWER LIMITED OUTPUTS. 12VDC	216.45
AX-OLS120	OLS120	12VDC OR 24VDC @ 4 AMP, 115VAC INPUT, AC AND BATTERY MONITORING.	251.08
AX-OLS180	OLS180	12VDC OR 24VDC @ 6 AMP, 115VAC INPUT, AC AND BATTERY MONITORING.	354.98
AX-OLS20	OLS20	12VDC @ 1 AMP OR 24VDC @ 500 MA, 115VAC INPUT	62.22
AX-OLS200	OLS200	12VDC @ 10 AMP, 115VAC INPUT, AC AND BATTERY MONITORING.	354.98
AX-OLS250	OLS250	24VDC @ 10 AMP, 115VAC INPUT, AC AND BATTERY MONITORING.	557.00
AX-OLS300	OLS300	12VDC @ 16 AMP, 115VAC INPUT, AC AND BATTERY MONITORING.	557.00
AX-OLS75	OLS75	12VDC OR 24VDC @ 2.5 AMP, 115VAC INPUT, AC AND BATTERY MONITORING.	202.02
AX-PD16W	PD16W	POWER DISTRIBUTION MODULE - CONVERTS ONE INPUT TO SIXTEEN (16) FUSE PROTECTED OUTPUTS. HANDLES UP TO 28VAC/VDC.	115.56
AX-PD4	PD4	POWER DISTRIBUTION MODULE - CONVERTS ONE INPUT TO FOUR (4) FUSE PROTECTED OUTPUTS	50.37
AX-PD4CB	PD4CB	POWER DISTRIBUTION MODULE - CONVERTS ONE INPUT TO FOUR (4) PTC PROTECTED OUTPUTS	50.37
AX-PD4UL	PD4UL	UL RECOGNIZED POWER DISTRIBUTION MODULE - CONVERTS ONE INPUT TO FOUR (4) FUSE PROTECTED OUTPUTS. HANDLES UP TO 28VAC/VD	56.30
AX-PD4ULCB	PD4ULCB	UL RECOGNIZED POWER DISTRIBUTION MODULE - CONVERTS ONE INPUT TO FOUR (4) PTC PROTECTED OUTPUTS. HANDLES UP TO 28VAC/VDC	56.30
AX-PD8	PD8	POWER DISTRIBUTION MODULE - CONVERTS ONE INPUT TO EIGHT (8) FUSE PROTECTED OUTPUTS.	65.19
AX-PD8CB	PD8CB	POWER DISTRIBUTION MODULE - CONVERTS ONE INPUT TO EIGHT (8) PTC PROTECTED OUTPUTS.	65.19

AX-PD8UL	PD8UL	UL RECOGNIZED POWER DISTRIBUTION MODULE - CONVERTS ONE INPUT TO EIGHT (8) FUSE PROTECTED OUTPUTS. HANDLES UP TO 28VAC/V	71.11
AX-PD8ULCB	PD8ULCB	UL RECOGNIZED POWER DISTRIBUTION MODULE - CONVERTS ONE INPUT TO EIGHT (8) PTC PROTECTED OUTPUTS. HANDLES UP TO 28VAC/VD	71.11
AX-PM212	PM212	12VDC @ 1 AMP, AC AND BATTERY MONITORING.	65.19
AX-PM224	PM224	24VDC @ 750MA, AC AND BATTERY MONITORING.	65.19
AX-PT2724	PT2724	TWO CHANNEL ANNUAL EVENT TIMER - 12 TO 24 VOLT AC OR DC OPERATION. 365 DAY/24 HR. TIMER. PROGRAMMABLE FEATURES PER CHAN	251.08
AX-PT724A	PT724A	SINGLE CHANNEL ANNUAL EVENT TIMER - 12 TO 24 VOLT AC OR DC OPERATION. 365 DAY/24 HR. TIMER. PROGRAMMABLE FEATURES: 50 I	167.39
AX-PT724AE	PT724AE	SINGLE CHANNEL ANNUAL EVENT TIMER - 12 TO 24 VOLT AC OR DC OPERATION. 365 DAY/24 HR. TIMER. PROGRAMMABLE FEATURES: 50 I	225.11
AX-R2416300UL	R2416300UL	SIXTEEN (16) FUSE PROTECTED OUTPUTS. 24VAC @ 12.5 AMP (300VA) OR 28VAC @ 10 AMP (280VA) 115VAC INPUT. 2U RACK MOUNT CHA	571.43
AX-R2416300ULCB	R2416300ULCB	SIXTEEN (16) PTC PROTECTED CLASS 2 RATED POWER LIMITED OUTPUTS. 24VAC @ 12.5 AMP (300VA) OR 28VAC @ 10 AMP (280VA) 115V	571.43
AX-R2416600UL	R2416600UL	SIXTEEN (16) FUSE PROTECTED OUTPUTS. 24VAC @ 25 AMP (600VA) OR 28VAC @ 20 AMP (560VA), 115VAC INPUT. 2U RACK MOUNT CHAS	655.56
AX-R2416600ULCB	R2416600ULCB	SIXTEEN (16) PTC PROTECTED CLASS 2 RATED POWER LIMITED OUTPUTS. 24VAC @ 25 AMP (600VA) OR 28VAC @ 20 AMP (560VA), 115VA	655.56
AX-R2416UL	R2416UL	SIXTEEN (16) FUSE PROTECTED OUTPUTS. 24VAC @ 7 AMP (175VA) OR 28VAC @ 6 AMP (175VA), 115VAC INPUT. 2U RACK MOUNT CHASSI	525.25
AX-R2416ULCB	R2416ULCB	SIXTEEN (16) PTC PROTECTED CLASS 2 RATED POWER LIMITED OUTPUTS. 24VAC @ 7 AMP (175VA) OR 28VAC @ 6 AMP (175VA), 115VAC	525.25
AX-R2416ULCBI	R2416ULCBI	SIXTEEN (16) ELECTRONICALLY ISOLATED PTC PROTECTED CLASS 2 RATED POWER LIMITED OUTPUTS RATED @ 1.56 AMP EACH. 24VAC @ 2	686.11
AX-R2416ULI	R2416ULI	SIXTEEN (16) ELECTRONICALLY ISOLATED FUSE PROTECTED CLASS 2 RATED POWER LIMITED OUTPUTS RATED @ 1.56 AMP EACH. 24VAC @	686.11
AX-R2432300UL	R2432300UL	THIRTY-TWO (32) FUSE PROTECTED OUTPUTS. 24VAC @ 12.5 AMP (300VA) OR 28VAC @ 10 AMP (280VA) 115VAC INPUT. 2U RACK MOUNT	700.00
AX-R2432300ULCB	R2432300ULCB	THIRTY-TWO (32) PTC PROTECTED CLASS 2 RATED POWER LIMITED OUTPUTS. 24VAC @ 12.5 AMP (300VA) OR 28VAC @ 10 AMP (280VA) 1	700.00
AX-R2432600UL	R2432600UL	THIRTY-TWO (32) FUSE PROTECTED OUTPUTS. 24VAC @ 25 AMP (600VA) OR 28VAC @ 20 AMP (560VA), 115VAC INPUT. 2U RACK MOUNT C	802.78

AX-R2432600ULCB	R2432600ULCB	THIRTY-TWO (32) PTC PROTECTED CLASS 2 RATED POWER LIMITED OUTPUTS. 24VAC @ 25 AMP (600VA) OR 28VAC @ 20 AMP (560VA), 11	802.78
AX-R248UL	R248UL	EIGHT (8) FUSE PROTECTED OUTPUTS. 24VAC @ 3.5 AMP (85VA) OR 28VAC @ 3 AMP (85VA), 115VAC INPUT. 2U RACK MOUNT CHASSIS F	395.38
AX-R248ULCB	R248ULCB	EIGHT (8) PTC PROTECTED CLASS 2 RATED POWER LIMITED OUTPUTS. 24VAC @ 3.5 AMP (85VA) OR 28VAC @ 3 AMP (85VA), 115VAC INP	395.38
AX-R248ULCBI	R248ULCBI	EIGHT (8) ELECTRONICALLY ISOLATED PTC PROTECTED CLASS 2 RATED POWER LIMITED OUTPUTS RATED @ 1.56 AMP EACH. 24VAC @ 12.5	519.48
AX-R248ULI	R248ULI	EIGHT (8) ELECTRONICALLY ISOLATED FUSE PROTECTED CLASS 2 RATED POWER LIMITED OUTPUTS RATED @ 1.56 AMP EACH. 24VAC @ 12.	519.48
AX-R615DC1016	R615DC1016	SIXTEEN (16) FUSE PROTECTED OUTPUTS. 6-15VDC @ 10 AMP, 115VAC INPUT. 2U RACK MOUNT CHASSIS FOR USE IN STANDARD EIA 19"	580.56
AX-R615DC1016CB	R615DC1016CB	SIXTEEN (16) PTC OUTPUTS. 6-15VDC @ 10 AMP. 2U RACK MOUNT CHASSIS FOR USE IN STANDARD EIA 19" RACK 3.25"H X 19.125"W X	580.56
AX-R615DC416UL	R615DC416UL	SIXTEEN (16) FUSE PROTECTED CLASS 2 RATED POWER LIMITED OUTPUTS. 6-15VDC @ 4 AMP, 115VAC INPUT. 2U RACK MOUNT CHASSIS F	542.57
AX-R615DC416ULCB	R615DC416ULCB	SIXTEEN (16) PTC CLASS 2 RATED POWER LIMITED OUTPUTS. 6-15VDC @ 4 AMP, 115VAC INPUT. 2U RACK MOUNT CHASSIS FOR USE IN S	542.57
AX-R615DC616UL	R615DC616UL	SIXTEEN (16) FUSE PROTECTED OUTPUTS. 6-15VDC @ 6 AMP, 115VAC INPUT. 2U RACK MOUNT CHASSIS FOR USE IN STANDARD EIA 19" R	571.43
AX-R615DC616ULCB	R615DC616ULCB	SIXTEEN (16) PTC CLASS 2 RATED POWER LIMITED OUTPUTS. 6-15VDC @ 6 AMP, 115VAC INPUT. 2U RACK MOUNT CHASSIS FOR USE IN S	571.43
AX-R615DC8UL	R615DC8UL	EIGHT (8) FUSE PROTECTED CLASS 2 RATED POWER LIMITED OUTPUTS. 6-15VDC @ 4 AMP, 115VAC INPUT. 2U RACK MOUNT CHASSIS FOR	525.25
AX-R615DC8ULCB	R615DC8ULCB	EIGHT (8) PTC CLASS 2 RATED POWER LIMITED OUTPUTS. 6-15VDC @ 4 AMP, 115VAC INPUT. 2U RACK MOUNT CHASSIS FOR USE IN STAN	525.25
AX-RAC120	RAC120	UL RECOGNIZED RELAY AND BASE - 120VAC OPERATION 10 AMP/120VAC/28VDC OR 10 AMP/277VAC DPDT CONTACTS. 30MA CURRENT DRAW.	41.48
AX-RAC24	RAC24	UL RECOGNIZED RELAY AND BASE - 24VAC OPERATION 10 AMP/120VAC/28VDC OR 10 AMP/277VAC DPDT CONTACTS. 50MA CURRENT DRAW.	41.48
AX-RB1224	RB1224	12VDC OR 24VDC OPERATION. 5 AMP/115VAC/28VDC DPDT CONTACTS. COIL DRAWS 50MA.	24.53
AX-RB30	RB30	12VDC OR 24VDC OPERATION. 30 AMP/115VAC.28VDC/277VAC SPDT CONTACT. HEAVY DUTY LOAD SWITCHING APPLICATIONS. COIL DRAWS 7	38.52
AX-RB5	RB5	6VDC OR 12VDC OPERATION. 5 AMP/115VAC/28VDC DPDT CONTACTS. COIL DRAWS 120MA.	24.53

AX-RB524	RB524	24VDC OPERATION. 5 AMP/115VAC/28VDC DPDT CONTACTS. COIL DRAWS 40MA.	24.53
AX-RB610	RB610	BREAK AWAY RELAY 6 PACK - 12VDC OR 24VDC OPERATION. 10 AMP/120VAC/28VDC SPDT CONTACT. COIL DRAWS 50MA.	71.11
AX-RB7	RB7	ULTRA SENSITIVE CLUSTER - 12VDC OR 24VDC OPERATION. SEVEN INDEPENDENT (3VDC TO 24VDC @ 2MA MINIMUM) POSITIVE TRIGGERS.	144.30
AX-RBOC7	RBOC7	OPEN COLLECTOR MODULE - 12VDC OR 24VDC OPERATION. SEVEN INDEPENDENT (3VDC TO 24VDC @ 2MA MINIMUM) POSITIVE TRIGGERS. SE	118.52
AX-RBR1224	RBR1224	ELECTRONIC RATCHET/TOGGLE RELAY - 12VDC TO 24VDC OPERATION. POSITIVE OR NEGATIVE ULTRA SENSITIVE TRIGGER. 2 AMP/115VAC/	53.33
AX-RBSN	RBSN	SENSITIVE RELAY - 12VDC OR 24VDC OPERATION. 2 AMP/115VAC/28VDC DPDT CONTACTS. 1,000 OHM COIL DRAWS ONLY 10MA.	24.53
AX-RBSNTTL	RBSNTTL	ULTRA-SENSITIVE RELAY - 12VDC TO 24VDC OPERATION. 3VDC TO 24VDC, 1MA POSITIVE OR NEGATIVE TRIGGER. 2 AMP/115VAC/28VDC D	35.56
AX-RBST	RBST	6VDC, 12VDC OR 24VDC OPERATION. 2 AMP/115VAC/28VDC DPDT CONTACTS. COIL DRAWS 25MA.	24.53
AX-RBTUL	RBTUL	ULTRA-SENSITIVE, 12VDC OR 24VDC OPERATION. 1 AMP/120VAC SPDT CONTACT. 3VDC TO 24VDC, 2MA POSITIVE TRIGGER. UL LISTED BU	41.48
AX-RBUL	RBUL	12VDC OR 24VDC OPERATION, 1 AMP/120VAC SPDT CONTACT. COIL DRAWS 30MA. UL LISTED BURG (UL749R). INCLUDES SNAP TRACK	25.81
AX-RDC12	RDC12	UL RECOGNIZED RELAY AND BASE - 12VDC OPERATION 10 AMP/120VAC/28VDC OR 10 AMP/277VAC DPDT CONTACTS. 80MA CURRENT DRAW.	41.48
AX-RDC24	RDC24	UL RECOGNIZED RELAY AND BASE - 24VDC OPERATION 10 AMP/120VAC/28VDC OR 10 AMP/277VAC DPDT CONTACTS. 40MA CURRENT DRAW.	41.48
AX-RDC48	RDC48	UL RECOGNIZED RELAY AND BASE - 48VDC OPERATION 10 AMP/120VAC/28VDC OR 10 AMP/277VAC DPDT CONTACTS. 20MA CURRENT DRAW.	41.48
AX-SMP10	SMP10	12VDC OR 24VDC @ 10 AMP BOARD.	277.06
AX-SMP10C12X	SMP10C12X	12VDC @ 10 AMP, 115VAC INPUT, GREY ENCLOSURE 13.5"H X 13"W X 3.25"D.	490.62
AX-SMP10C24X	SMP10C24X	24VDC @ 10 AMP, 115VAC INPUT, GREY ENCLOSURE 15.5â€H X 12â€W X 4.5â€D.	669.44
AX-SMP10PM	SMP10PM	12VDC OR 24VDC @ 10 AMP BOARD, AC AND BATTERY MONITORING.	323.23
AX-SMP10PM12P16	SMP10PM12P16	12VDC @ 10 AMP, 115VAC INPUT, AC AND BATTERY MONITORING. SIXTEEN (16) FUSE PROTECTED OUTPUTS, GREY ENCLOSURE 13.5"H X 1	627.78
AX-SMP10PM12P16CB	SMP10PM12P16CB	12VDC @ 10 AMP, 115VAC INPUT, AC AND BATTERY MONITORING. SIXTEEN (16) PTC PROTECTED OUTPUTS, GREY ENCLOSURE 13.5"H X 13	627.78

AX-SMP10PM12P4	SMP10PM12P4	12VDC @ 10 AMP, 115VAC INPUT, AC AND BATTERY MONITORING. FOUR (4) FUSE PROTECTED OUTPUTS, GREY ENCLOSURE 13.5"H X 13"W	555.56
AX-SMP10PM12P4CB	SMP10PM12P4CB	12VDC @ 10 AMP, 115VAC INPUT, AC AND BATTERY MONITORING. FOUR (4) PTC PROTECTED OUTPUTS, GREY ENCLOSURE 13.5"H X 13"W X	555.56
AX-SMP10PM12P8	SMP10PM12P8	12VDC @ 10 AMP, 115VAC INPUT, AC AND BATTERY MONITORING. EIGHT (8) FUSE PROTECTED OUTPUTS, GREY ENCLOSURE 13.5"H X 13"W	566.67
AX-SMP10PM12P8CB	SMP10PM12P8CB	12VDC @ 10 AMP, 115VAC INPUT, AC AND BATTERY MONITORING. EIGHT (8) PTC PROTECTED OUTPUTS, GREY ENCLOSURE 13.5"H X 13"W	566.67
AX-SMP10PM24P16	SMP10PM24P16	24VDC @ 10 AMP, 115VAC INPUT, AC AND BATTERY MONITORING. SIXTEEN (16) FUSE PROTECTED OUTPUTS, GREY ENCLOSURE 15.5"H X 12	872.22
AX-SMP10PM24P16CB	SMP10PM24P16CB	24VDC @ 10 AMP, 115VAC INPUT, AC AND BATTERY MONITORING. SIXTEEN (16) PTC PROTECTED OUTPUTS, GREY ENCLOSURE 15.5"H X 12	872.22
AX-SMP10PM24P4	SMP10PM24P4	24VDC @ 10 AMP, 115VAC INPUT, AC AND BATTERY MONITORING. FOUR (4) FUSE PROTECTED OUTPUTS, GREY ENCLOSURE 15.5"H X 12"W	822.22
AX-SMP10PM24P4CB	SMP10PM24P4CB	24VDC @ 10 AMP, 115VAC INPUT, AC AND BATTERY MONITORING. FOUR (4) PTC PROTECTED OUTPUTS, GREY ENCLOSURE 15.5"H X 12"W X	822.22
AX-SMP10PM24P8	SMP10PM24P8	24VDC @ 10 AMP, 115VAC INPUT, AC AND BATTERY MONITORING. EIGHT (8) FUSE PROTECTED OUTPUTS, GREY ENCLOSURE 15.5"H X 12"W	783.33
AX-SMP10PM24P8CB	SMP10PM24P8CB	24VDC @ 10 AMP, 115VAC INPUT, AC AND BATTERY MONITORING. EIGHT (8) PTC PROTECTED OUTPUTS, GREY ENCLOSURE 15.5"H X 12"W	783.33
AX-SMP10PMC12X	SMP10PMC12X	12VDC @ 10 AMP, 115VAC INPUT, AC AND BATTERY MONITORING, GREY ENCLOSURE 13.5"H X 13"W X 3.25"D.	536.80
AX-SMP10PMC24X	SMP10PMC24X	24VDC @ 10 AMP, 115VAC INPUT, AC AND BATTERY MONITORING, GREY ENCLOSURE 15.5"H X 12"W X 4.5"D.	713.89
AX-SMP16PMC12X	SMP16PMC12X	12VDC @ 16 AMP, 115VAC INPUT, AC AND BATTERY MONITORING, GREY ENCLOSURE 15.5"H X 12"W X 4.5"D.	713.89
AX-SMP3	SMP3	6VDC, 12VDC OR 24VDC @ 2.5 AMP.	77.04
AX-SMP312C	SMP312C	12VDC @ 2.5 AMP, 12VDC/4AH BATTERY & 16.5VAC/40VA PLUG-IN TRANSFORMER.	158.73
AX-SMP312CX	SMP312CX	12VDC @ 2.5 AMP, 12VDC/7AH BATTERY & 16.5VAC/40VA PLUG-IN TRANSFORMER.	164.50
AX-SMP3E	SMP3E	6VDC, 12VDC OR 24VDC @ 2.5 AMP, GREY ENCLOSURE 8.5"H X 7.5"W X 3.5"D.	124.44
AX-SMP3PM	SMP3PM	12VDC OR 24VDC @ 2.5 AMP, AC AND BATTERY MONITORING.	112.59
AX-SMP3PMCTX	SMP3PMCTX	12VDC OR 24VDC @ 2.5 AMP, 115VAC INPUT, AC AND BATTERY MONITORING, GREY ENCLOSURE 13.5"H X 13"W X 3.25"D.	308.80
AX-SMP3WP	SMP3WP	SINGLE OUTPUT, 6, 12 OR 24VDC @ 2.5 AMP, 115VAC INPUT. NEMA 4 OUTDOOR ENCLOSURE 12"H X 8"W X 6"D.	386.72

AX-SMP5	SMP5	6VDC, 12VDC OR 24VDC @ 4 AMP BOARD.	109.63
AX-SMP5PM	SMP5PM	12VDC OR 24VDC @ 4 AMP, AC AND BATTERY MONITORING.	150.07
AX-SMP5PMCTX	SMP5PMCTX	12VDC OR 24VDC @ 4 AMP, 115VAC INPUT, AC AND BATTERY MONITORING, GREY ENCLOSURE 13.5"H X 13"W X 3.25"D.	352.09
AX-SMP5WP	SMP5WP	SINGLE OUTPUT, 12 OR 24VDC @ 4 AMP, 115VAC INPUT. NEMA 4 OUTDOOR ENCLOSURE 12"H X 8"W X 6"D.	450.22
AX-SMP7	SMP7	12VDC OR 24VDC @ 6 AMP BOARD.	190.48
AX-SMP7CTX	SMP7CTX	12VDC OR 24VDC @ 6 AMP, 115VAC INPUT, GREY ENCLOSURE 13.5"H X 13"W X 3.25"D.	412.70
AX-SMP7PM	SMP7PM	12VDC OR 24VDC @ 6 AMP BOARD, AC AND BATTERY MONITORING.	225.11
AX-SMP7PMCTX	SMP7PMCTX	12VDC OR 24VDC @ 6 AMP, 115VAC INPUT, AC AND BATTERY MONITORING, GREY ENCLOSURE 13.5"H X 13"W X 3.25"D.	450.22
AX-SMP7WP	SMP7WP	SINGLE OUTPUT, 12 OR 24VDC @ 6 AMP, 115VAC INPUT. NEMA 4 OUTDOOR ENCLOSURE 12"H X 8"W X 6"D.	571.43
AX-SPACER1	SPACER1	5/8" NYLON SPACER. PACKAGE OF 25	14.16
AX-ST1	ST1	SNAP TRACK MOUNTING FOR: RB5, RBSN, RBST, RB30, RB524, RB1224, RBSNTTL.	4.53
AX-ST2	ST2	SNAP TRACK MOUNTING FOR: RB7, RBOC7.	11.32
AX-ST3	ST3	SNAP TRACK MOUNTING FOR: SMP3, SMP5, AL624, 6062, PT724, PT724A.	15.11
AX-STRIKEIT1	STRIKEIT1	TWO (2) 24VDC INDEPENDENTLY OR SIMULTANEOUSLY CONTROLLED LOCK OUTPUTS FOR PANIC HARDWARE DEVICES WITH VERY HIGH INRUSH	700.00
AX-T16100	T16100	16.5VAC/100VA, 120VAC INPUT	97.78
AX-T1656	T1656	16VAC/56VA, 120VAC INPUT.	74.07
AX-T24130D	T24130D	24VAC/100VA, 120VAC OR 220VAC INPUT.	77.04
AX-T2428100	T2428100	24VAC/100VA OR 28VAC/100VA, 120VAC INPUT	77.04
AX-T2428100C	T2428100C	24VAC OR 28VAC/100VA, 120VAC INPUT, RED ENCLOSURE 5.625"H X 7"W X 4.5"D	158.73
AX-T2428100WP	T2428100WP	SINGLE OUTPUT, 24VAC @ 4 AMP (100VA) OR 28VAC @ 3.5 AMP (100VA), 115VAC INPUT. NEMA 4 OUTDOOR ENCLOSURE 12"H X 8"W X 6"	251.08
AX-T2428175	T2428175	24 VAC @ 7.25A OR 28VAC @ 6.25A, 120VAC INPUT.	103.70
AX-T2428175C	T2428175C	24VAC OR 28VAC 175VA, 120VAC INPUT, RED ENCLOSURE 5.625"H X 7"W X 4.5"D.	178.93
AX-T2428175WP	T2428175WP	24 VAC @ 7.25A OR 28VAC @ 6.25A, 120VAC INPUT. NEMA 4 OUTDOOR ENCLOSURE 12"H X 8"W X 6"D.	274.17
AX-T2428300	T2428300	24VAC/300VA OR 28VAC/300VA, 120VAC INPUT	245.31
AX-T2428300E	T2428300E	24VAC OR 28VAC/300VA, 120VAC INPUT, GREY ENCLOSURE 12.25"H X 7.75"W X 4.5"D.	334.78
AX-T2428300WP	T2428300WP	SINGLE OUTPUT, 24VAC @ 14 AMP (300VA) OR 28VAC @ 12.5 AMP (300VA), 115VAC INPUT. NEMA 4 OUTDOOR ENCLOSURE 12"H X 8"W X	432.90
AX-T28140D	T28140D	28VAC/175VA , 120VAC OR 220VAC INPUT.	115.56
AX-T2856	T2856	28VAC/56VA, 120VAC INPUT.	74.07
AX-T2856C	T2856C	28VAC/56VA, 120VAC INPUT, RED ENCLOSURE 5.625"H X 7"W X 4.5"D.	158.73
AX-T2885D	T2885D	28VAC/100VA, 120VAC OR 220VAC INPUT.	85.93

AX-TAPE1	TAPE1	DOUBLE STICK TAPE PADS PACKAGE OF 25	20.77
AX-TEMPO2	TEMPO2	UNIVERSAL TWO STAGE TIMER, 12 OR 24 VOLTS AC OR DC OPERATION, 1-60 SECONDS TIMED DOOR RELEASE, DAILY WEEKLY TEST MODE,	103.70
AX-TP1220	TP1220	12VAC/20VA, 120VAC INPUT.	17.75
AX-TP1620	TP1620	16VAC/20VA, 120VAC INPUT.	17.75
AX-TP1640	TP1640	16VAC/40VA, 120VAC INPUT.	22.64
AX-TP1650	TP1650	16VAC 50VA, 120VAC INPUT.	24.86
AX-TP2420	TP2420	24VAC/20VA, 120VAC INPUT.	19.44
AX-TP2440	TP2440	24VAC/40VA, 120VAC INPUT.	22.64
AX-TP2450	TP2450	24VAC/50VA, 120VAC INPUT.	26.43
AX-VB1	VB1	12-24VDC INPUT TO REGULATED 24VDC @ .75 AMP OUTPUT. MODULAR CONNECTOR/CABLE ASSEMBLY. HIGH IMPACT INSULATED HOUSING.	68.15
AX-VB1T	VB1T	12-24VDC INPUT TO REGULATED 24VDC @ .75 AMP OUTPUT. SCREW TERMINAL BLOCK. HIGH IMPACT INSULATED HOUSING.	62.22
AX-VR1	VR1	24VAC OR 24VDC INPUT TO 12VDC @ 1 AMP OUTPUT. MODULAR CONNECTOR/CABLE ASSEMBLY. HIGH IMPACT INSULATED HOUSING.	68.15
AX-VR1T	VR1T	24VAC OR 24VDC INPUT TO 12VDC @ 1 AMP OUTPUT WITH SCREW TERMINALS. HIGH IMPACT INSULATED HOUSING.	62.22
AX-VR2T	VR2T	24VAC OR 24VDC INPUT TO 12VDC @ .5 AMP OUTPUT W/SCREW TERMINALS. HIGH IMPACT INSULATED HOUSING.	50.37
AX-WP1	WP1	NEMA 4/IP65 OUTDOOR RATED ENCLOSURE. ENCLOSURE 12"H X 7.75"W X 6"D.	202.02
AX-WPTV244175UL	WPTV244175UL	THREE (3) PTC CLASS 2 RATED POWER LIMITED OUTPUTS RATED @ 2.5 AMP AND ONE (1) 10 AMP FUSE OUTPUT. 24VAC @ 7 AMP (175VA)	308.80
AX-WPTV244300UL	WPTV244300UL	THREE (3) PTC CLASS 2 RATED POWER LIMITED OUTPUTS RATED @ 2.5 AMP AND ONE (1) 15 AMP FUSE OUTPUT. 24VAC @ 12.5 AMP (300)	378.07
AX-WPTV248175UL	WPTV248175UL	EIGHT (8) FUSE PROTECTED OUTPUTS. 24VAC @ 7 AMP (175VA) OR 28VAC @ 6.25 AMP (175VA). 115VAC INPUT. NEMA 4 OUTDOOR ENCL	340.55
AX-WPTV248175ULCB	WPTV248175ULCB	EIGHT (8) PTC CLASS 2 RATED POWER LIMITED OUTPUTS. 24VAC @ 7 AMP (175VA) OR 28VAC @ 6.25 AMP (175VA). 115VAC INPUT. NEMA 4 OUTDOOR ENCL	340.55
AX-WPTV248300UL	WPTV248300UL	EIGHT (8) FUSE PROTECTED OUTPUTS. 24VAC @ 12.5 AMP (300VA) OR 28VAC @ 10 AMP (280VA). CULUS LISTED. NEMA 4 OUTDOOR ENCL	409.81
AX-WPTV248300ULCB	WPTV248300ULCB	EIGHT (8) PTC CLASS 2 RATED POWER LIMITED OUTPUTS. 24VAC @ 12.5 AMP (300VA) OR 28VAC @ 10 AMP (280VA). NEMA 4 OUTDOOR ENCL	409.81
AX-WPTV248UL	WPTV248UL	EIGHT (8) FUSE PROTECTED OUTPUTS. 24VAC @ 3.5 AMP (85VA), 115VAC INPUT. NEMA 4 OUTDOOR ENCLOSURE 12"H X 8"W X 6"D. UL L	320.35
AX-WPTV248ULCB	WPTV248ULCB	EIGHT (8) PTC CLASS 2 RATED POWER LIMITED OUTPUTS. 24VAC @ 3.5 AMP (85VA), 115VAC INPUT. NEMA 4 OUTDOOR ENCLOSURE 12"H	320.35