

| MODEL #      | MANUFACTURER # | DESCRIPTION  | MSRP   |
|--------------|----------------|--|--------|
| CNB-A1268NL  | A1268NL        | 22x Zoom camera(With Digital Slow Shutter)<br>1/4" SONY Super HAD CCD,<br>22x Zoom (Digital 10x), 410K Pixels,<br>Day&Night(Digital Slow Shutter), RS-485 & PTZ Control, 12VDC/24VAC                     | 576.08 |
| CNB-A1568NL  | A1568NL        | 30x Zoom Camera (Dual Voltage)<br>1/4" SONY Super HAD CCD, 480TVL,<br>30x Optical Zoom(Digital 10x), Day&Night(ICR),<br>DSS, OSD, RS-485(Pelco-D)/PTZ Controller Interface,<br>24VAC/1 2VDC Dual Voltage | 727.86 |
| CNB-AN127L   | AN127L         | 16x Zoom camera(With Digital Slow Shutter)<br>1/4" SONY Super HAD CCD,<br>16x Zoom (Digital 12x), 410K Pixels,<br>Day&Night(Digital Slow Shutter), RS-485 & PTZ Control, 12VDC/24VAC DUAL VOLTAGE        | 556.71 |
| CNB-AN302L   | AN302L         | 12x Zoom camera(With Digital Slow Shutter)<br>1/3" SONY Super HAD CCD, RS-485<br>12x Zoom (Digital 10x), 410K Pixels,<br>Day&Night(Digital Slow Shutter), RS-485, DC1 2V                                 | 755.72 |
| CNB-AN808    | AN808          | 26x Zoom camera, PTZ control<br>1/4" SONY Super HAD CCD, 410K Pixels,<br>26x Zoom(Digital 10x), Day&Night(IR cut filter removable),<br>RS-485, PTZ Control, 12VDC/24VAC Dual Voltage                     | 746.44 |
| CNB-B1000N43 | B1000N43       | Weather Proof IR Camera(2boards)<br>1/3" SONY Super HAD CCD, 270K Pixels, 4.3mm Fixed Lens<br>12 IR LED's, 1 CdS, 850nm 30 degree @ 850 nm(Distance 15 meter), DC12V, Diameter : 50mm                    | 174.55 |
| CNB-B1000N6  | B1000N6        | Weather Proof IR Camera(2boards)<br>1/3" SONY Super HAD CCD, 270K Pixels, 6mm Fixed Lens<br>12 IR LED's, 1 CdS, 850nm 30 degree @ 850 nm(Distance 15 meter), DC12V, Diameter : 50mm                      | 174.55 |
| CNB-B1700N43 | B1700N43       | Weather Proof IR Camera(1 board)<br>1/3" SONY Super HAD CCD, 270K Pixels, 4.3mm Fixed Lens<br>12 IR LED's, 1 CdS, 850nm 30 degree @ 850 nm(Distance 15 meter), DC12V, Diameter : 50mm                    | 164.50 |
| CNB-B1700N6  | B1700N6        | Weather Proof IR Camera(1 board)<br>1/3" SONY Super HAD CCD, 270K Pixels, 4.3mm or 6mm Fixed Lens<br>12 IR LED's, 1 CdS, 850nm 30 degree @ 850 nm(Distance 15 meter), DC12V, Diameter : 50mm             | 164.50 |
| CNB-B1710N43 | B1710N43       | Weather Proof IR Camera<br>1/3" SONY Super HAD CCD, 410K Pixels, 4.3mm Fixed Lens<br>12 IR LED's, 1 CdS, 850nm 30 degree @ 850 nm(Distance 15 meter), DC12V, Diameter : 50mm                             | 223.03 |
| CNB-B1710N6  | B1710N6        | Weather Proof IR Camera<br>1/3" SONY Super HAD CCD, 410K Pixels, 6mm Fixed Lens<br>12 IR LED's, 1 CdS, 850nm 30 degree @ 850 nm(Distance 15 meter), DC12V, Diameter : 50mm                               | 223.03 |

|                          |                      |  |         |
|--------------------------|----------------------|--|---------|
| CNB-B2000N               | B2000N               | Weather Proof IR Camera(380TVL)<br>1/3° SONY Super HAD CCD, 12mm Fixed Lens,<br>34 IR LED's, 1 CdS, 850 nm 15 degree @ 850 nm(Distance 30 meter),<br>DC12V, Diameter : 65mm  | 203.64  |
| CNB-B2310N               | B2310N               | Weather Proof IR Camera(550TVL)<br>1/3° SONY Super HAD CCD, 410K Pixels, 6mm Fixed Lens,<br>34 IR LED's, 1 CdS, 850 nm 15 degree @ 850 nm(Distance 30 meter),<br>DC12V, Diameter : 65mm  | 325.02  |
| CNB-B2310NVF             | B2310NVF             | Weather Proof IR Camera(550TVL,ICR)<br>1/3° SONY Super HAD CCD, 410K Pixels, 3.8~9.5 mm Lens,<br>18 IR LED's, 1 CdS, 850 nm 15 degree @ 850 nm(Distance 15 meter),<br>DC1 2V, Diameter : 65mm  | 456.94  |
| CNB-BDF0303              | BDF0303              | 4CH Capture Board<br>Display/Recording Speed 30fps/30fps<br>Enhanced MPEG-2/4 Codec, Average Image Size 2KB<br>320x240/640x480(NTSC), 320x288/640x576(PAL)<br>Network connection via TCP/IP, RS-422/485  | 210.10  |
| CNB-BDS0606              | BDS0606              | 1 6CH Capture Board<br>Display/Recording Speed 60fps/60fps<br>Enhanced MPEG-4 Codec, Average Image Size 2KB<br>320x240/720x480(NTSC), 320x288/720x576(PAL)<br>Network connection via TCP/IP, RS-422/485  | 434.43  |
| CNB-BDS1212              | BDS1212              | 16CH Capture Board<br>Display/Recording Speed 120fps/120fps<br>Enhanced MPEG-2/4 Codec, Average Image Size 2KB<br>320x240/720x480(NTCS), 320x288/720x576(PAL)<br>Network connection via TCP/IP, 480fps Display(Optional)   | 563.15  |
| CNB-BDS2424              | BDS2424              | 16CH Capture Board<br>Display/Recording Speed 240fps/240fps<br>Enhanced MPEG-2/4 Codec, Average Image Size 2KB<br>320x240/720x480(NTCS), 320x288/720x576(PAL)<br>Network connection via TCP/IP, 480fps Display(Optional)   | 1084.03 |
| CNB-BE3815NVR            | BE3815NVR            | Wheatherproof IR Camera (550TVL, SDNR, D&N, DSS)<br>1/3" SONY Super HAD CCD, 550TVL,<br>SDNR, 0.00Lux(IR LED On), Weatherproof<br>AWB, AGC On/Off, BLC On/Off, Flickerless On/Off,<br>D&N(ICR) On/Off, DSS On/Off, 2x Digital Zoom On/Off<br>42 LEDs, 1 CdS Sensor, 24VAC/1 2VDC<br>IR LED's Visibility Range : 40 meter (850 nm, 30?)<br>Built-in Fan & Heater, Service Extra-Video out | 681.39  |
| CNB-BE4810NCR<br>75~50mm | BE4810NCR<br>75~50mm | Wheatherproof IR Camera (550TVL, SDNR, D&N, DSS)<br>1/3° SONY Super HAD CCD, 550TVL,<br>SDNR, 0.00Lux(IR LED On), Weatherproof<br>AWB, AGC On/Off, BLC On/Off, Flickerless On/Off,<br>D&N(ICR) On/Off, DSS On/Off, 2x Digital Zoom On/Off<br>9 Hybrid IR LEDs, 1 CdS Sensor<br>IR LED's Visibility Range : 60 meter (850 nm, 15?)<br>Built-in Fan & Heater, Service Extra-Video out      | 1084.03 |

|               |           |   |         |
|---------------|-----------|---|---------|
| CNB-BE4815NVR | BE4815NVR | Weatherproof IR Camera (550TVL, SDNR, D&N, DSS)<br>1/3" SONY Super HAD CCD, 550TVL,<br>SDNR, 0.00Lux(IR LED On), Weatherproof<br>AWB, AGC On/Off, BLC On/Off, Flickerless On/Off,<br>D&N(ICR) On/Off, DSS On/Off, 2x Digital Zoom On/Off<br>56 LEDs, 1 CdS Sensor, 24VAC/1 2VDC Dual Voltage<br>IR LED's Visibility Range : 50 meter (850 nm, 15?, 30? mixed)<br>Built-in Fan & Heater                        | 761.92  |
| CNB-BE5810NCR | BE5810NCR | Weatherproof IR Camera (550TVL, SDNR, D&N, DSS)<br>1/3" SONY Super HAD CCD, 550TVL, 0.00Lux(IR LED On),<br>SDNR, 0.00Lux(IR LED On), Weatherproof,<br>AWB, AGC On/Off, BLC On/Off, Flickerless On/Off,<br>D&N(ICR) On/Off, DSS On/Off, 2x Digital Zoom On/Off<br>126 LEDs, 1 CdS Sensor, Built-in Fan & Heater,<br>IR LED's Visibility Range : 50 meter (850 nm, 15?)<br>Service Extra-Video out              | 1201.72 |
| CNB-BE5815NVR | BE5815NVR | Weatherproof IR Camera (550TVL, SDNR, D&N, DSS)<br>1/3" SONY Super HAD CCD, 550TVL,<br>SDNR, 0.00Lux(IR LED On), Weatherproof<br>AWB, AGC On/Off, BLC On/Off, Flickerless On/Off,<br>D&N(ICR) On/Off, DSS On/Off, 2x Digital Zoom On/Off<br>34 LEDs, 1 CdS Sensor, 24VAC/1 2VDC, Line-lock<br>IR LED's Visibility Range : 20 meter (850 nm, 15?, 30? mixed)<br>Built-in Fan & Heater, Service Extra-Video out | 802.19  |
| CNB-BM4267NL  | BM4267NL  | Weatherproof I R Camera (480TVL, 220x Zoom, OSD, DSS)<br>1/4" SONY Super HAD CCD, 480TVL, 0.001 Lux,<br>22x Optical Zoom(Digital 10x), DSS, OSD, 24VAC/1 2VDC<br>RS-485(Pelco-D), Built-in Heater   | 882.72  |
| CNB-BM5562NIR | BM5562NIR | Weatherproof IR Camera (480TVL, 300x Zoom, OSD, D&N, DSS)<br>1/4" SONY Super HAD CCD, 480TVL, 0.00Lux(IR LED On)<br>30x Optical Zoom(Digital 10x), Day&Night(ICR),<br>DSS, OSD, RS-485(Pelco-D), Weatherproof,<br>126 LEDs, 1 CdS Sensor, Built-in Fan & Heater,<br>IR LED's Visibility Range : 50 meter (850 nm, 15?)<br>Service Extra-Video out   | 1325.61 |
| CNB-BN258IR   | BN258IR   | IR Bullet Camera<br>1/3" SONY Super HAD CCD, 270K Pixels,<br>0.1 lx, 6mm lens, DC12V,<br>AWB, AGC On/Off, BLC On/Off  | 216.57  |
| CNB-CN258IR   | CN258IR   | Bustop(for Vehicle)<br>1/3" SONY Super HAD CCD, 270K Pixels,<br>2.5mm lens, DC1 2V, 11 LEDs, 1 CdS Sensor, Audio<br>Visibility Range : 5 meter (940 nm, 20 degree),   | 232.73  |
| CNB-CVB100    | CVB100    | Ceiling Mount Bracket for Vandal Proof Dome Camera  | 54.46   |
| CNB-D1000N    | D1000N    | Dome camera<br>1/3" SONY Super HAD CCD, 270K Pixels, 0.1 lx, 3.8 mm lens<br>AWB, AGC On/off, BLC On/off, 85mm dome size, DC12V, 2 boards  | 145.24  |
| CNB-D1000NDF  | D1000NDF  | Dome camera(IR Filter Day&Night)<br>1/3" SONY Super HAD CCD, 270K Pixels, 0.1 lx, 3.8 mm lens<br>AWB, AGC On/off, BLC On/off, 85mm dome size, DC12V, 2 boards   | 151.34  |

|              |          |   |        |
|--------------|----------|---|--------|
| CNB-D1310N   | D1310N   | Dome camera(550TVL)<br>1/3" SONY Super HAD CCD, 410K Pixels, 0.3 lx, 3.8 mm lens<br>AWB, AGC On/off, BLC On/off, 85mm dome size, DC12V  | 229.49 |
| CNB-D1700N   | D1700N   | Dome camera<br>1/3" SONY Super HAD CCD, 270K Pixels, 0.1 lx, 3.8 mm lens<br>AWB, AGC On/off, BLC On/off, 85mm dome size, DC12V, 1 board   | 138.07 |
| CNB-D1710N   | D1710N   | Dome camera<br>1/3" SONY Super HAD CCD, 410K Pixels, 0.3 lx, 3.8 mm lens<br>AWB, AGC On/off, BLC On/off, 85mm dome size, DC12V, 1 board   | 177.78 |
| CNB-D2000NIR | D2000NIR | IR Dome camera(380TVL)<br>1/3" SONY CCD, 3.8mm lens, 24 LEDs, 1 CdS Sensor, DC12V, Visibility Range : 850 nm, 30 degree(10 meter)   | 200.40 |
| CNB-D2005N   | D2005N   | Dome camera(3-Axis)<br>1/3" SONY Super HAD CCD, 270K Pixels, 0.1 lx, 3.8 mm lens<br>AWB, AGC On/off, BLC On/off, Service Video Out,<br>100mm dome size, 1 2VDC/24VAC Dual Voltage   | 177.78 |
| CNB-D2005NVD | D2005NVD | Dome camera(3-Axis)<br>1/3" SONY Super HAD CCD, 270K Pixels, Vari Focal lens(4-9mm)<br>AWB, AGC On/off, BLC On/off, Service Video Out,<br>100mm dome size, 1 2VDC/24VAC Dual Voltage  | 252.12 |
| CNB-D2265NVF | D2265NVF | Dome Camera(3-Axis, WDR, ICR, OSD)<br>1/3" SONY Double Scan CCD, 410K Pixels, Vari-focal Lens(3.8~9.5mm) Lens,<br>0.001 Lux(Color), 0.0003 Lux(B/W), OSD, WDR On/Off,AGC On/Off,<br>BLC On/Off, Flickerless On/Off, Service Video Out, 1 2VDC/24VAC Dual Voltage, Dome size : 100mm   | 616.36 |
| CNB-D2310NIR | D2310NIR | IR Dome camera(550TVL)<br>1/3" SONY CCD, 3.8mm lens, 24 LEDs, 1 CdS Sensor, DC12V, Visibility Range : 850 nm, 30 degree(10 meter)   | 307.07 |
| CNB-D2315NVD | D2315NVD | Dome Camera(3-Axis, 550TVL)<br>1/3" SONY Super HAD CCD, 550TVL, 410K Pixels, Vari-focal Lens(4-9mm), 0.3 Lux, AGC On/Off, BLC On/Off,Flickerless<br>On/Off, Service Video Out, Dome size : 100mm, 1 2VDC/24VAC Dual Voltage   | 360.40 |
| CNB-D2315NVF | D2315NVF | Dome Camera(3-Axis, 550TVL, Day&Night)<br>1/3" SONY Super HAD CCD, 550TVL, 410K Pixels, Vari-focal Lens(3.8~9.5mm), 0.3 Lux(Color), 0.05 Lux(B/W), AWC, AGC<br>On/Off, BLC On/Off, Flickerless On/Off, Service Video Out,<br>1 2VDC/24VAC Dual Voltage, Dome size : 100mm   | 421.56 |
| CNB-D2815NVD | D2815NVD | Dome Camera(3-Axis, 550TVL, DSS, SDNR)<br>1/3" SONY Super HAD CCD, 550TVL, 410K Pixels, Vari-focal Lens(4-9mm), 0.001 Lux, AGC On/Off, BLC On/Off, Flickerless<br>On/Off, DSS, SDNR, Service Video Out, Dome size : 100mm, 1 2VDC/24VAC Dual Voltage  | 382.94 |
| CNB-D2815NVF | D2815NVF | Dome Camera(3-Axis, 550TVL, Day&Night, DSS, SDNR)<br>1/3" SONY Super HAD CCD, 550TVL, 410K Pixels, Vari-focal Lens(3.8~9.5mm), 0.0003 Lux, AWC, AGC On/Off, BLC On/Off,<br>Flickerless On/Off, DSS, SDNR, Service Video Out, 1 2VDC/24VAC Dual Voltage, Dome size : 100mm   | 444.07 |
| CNB-D2815NVR | D2815NVR | IR Dome Camera (550TVL, SDNR, D&N, DSS, Vari-focal Lens)<br>1/3" SONY Super HAD CCD, 550TVL, SDNR, 0.00Lux(IR LED On)<br>AWB, AGC On/Off, BLC On/Off, Flickerless On/Off,<br>D&N(ICR) On/Off, DSS On/Off, 2x Digital Zoom On/Off<br>100mm dome size, 3-Axis, 20 LEDs, 1 CdS Sensor, IR LED's Visibility Range : 15 meter (850nm, 30?), Service Extra-Video out,<br>12VDC(Audio Function Optional) | 492.35 |
| CNB-D2965NVD | D2965NVD | Color Dome Camera (530TVL, SDNR, OSD, DSS)<br>1/3" SONY Super HAD CCD, 530TVL, Color/BW, 4-9mm Varifocal Lens, WB(ATW/ATC/Manual), AGC, BLC, Flickerless, OSD,<br>SDNR, DSS, Service Extra-Video out, 3-Axis, 100mm dome size, Dual Voltage<br>(Audio Function Optional)  | 392.58 |

|              |          |   |        |
|--------------|----------|---|--------|
| CNB-D3700N   | D3700N   | Dome camera(380TVL)<br>1/3" SONY Super HAD CCD, 270K Pixels, 0.1 lx, 3.8 mm lens<br>AWB, AGC On/off, BLC On/off, 68mm dome size, DC12V  | 127.73 |
| CNB-D3710N   | D3710N   | Dome camera(480TVL)<br>1/3" SONY Super HAD CCD, 410K Pixels, 0.3 lx, 3.8 mm lens<br>AWB, AGC On/off, BLC On/off, 68mm dome size, DC12V  | 174.55 |
| CNB-DIO0804  | DIO0804  | DI/DO Board(8 Input/4 Output)<br>For CNB DVR Capture Board  | 106.22 |
| CNB-DIO1608  | DIO1608  | DI/DO Board(16 Input/8 Output)For CNB DVR Capture Board   | 193.94 |
| CNB-G1315N   | G1315N   | Standard Color Camera(550TVL)<br>1/3" SONY Super HAD CCD, 550TVL, 410K Pixels,<br>DC/Video Iris, 0.3 Lux, AWC, AGC On/Off, BLC On/Off, 12VDC/24VAC Dual Voltage   | 300.61 |
| CNB-G1315NF  | G1315NF  | Standard Color Camera(550TVL, ICR)<br>1/3" SONY Super HAD CCD, 550TVL, 410K Pixels,<br>DC/Video Iris, 0.3 Lux, D&N(ICR), AWC, AGC On/Off, BLC On/Off, 1 2VDC/24VAC Dual Voltage                             | 337.89 |
| CNB-G1815N   | G1815N   | Standard Color Camera(550TVL, DSS, SDNR)<br>1/3" SONY Super HAD CCD, 550TVL, 410K Pixels,<br>DC/Video Iris, 0.001 Lux, AWC, AGC On/Off, BLC On/Off,<br>DSS, SDNR, 1 2VDC/24VAC Dual Voltage                 | 320.00 |
| CNB-G1815NF  | G1815NF  | Standard Color Camera(550TVL, DSS, SDNR, D&N)<br>1/3" SONY Super HAD CCD, 550TVL, 410K Pixels,<br>DC/Video Iris, 0.0003 Lux, D&N(ICR), AWC, AGC On/Off,<br>BLC On/Off, DSS, SDNR, 1 2VDC/24VAC Dual Voltage | 360.40 |
| CNB-G1965N   | G1965N   | Color Box Camera (530TVL, SDNR, OSD, DSS)<br>1/3" SONY Super HAD CCD, 530TVL, Color/BW<br>C/CS Mount, ALC(Video/DC)/ELC, OSD, SDNR, DSS<br>WB(ATW/ATC/Manual), AGC, BLC, Flickerless                        | 328.23 |
| CNB-G1965NF  | G1965NF  | Color Box Camera (530TVL, SDNR, OSD, DSS, ICR)<br>1/3" SONY Super HAD CCD, 530TVL, Color/BW<br>C/CS Mount, ALC(Video/DC)/ELC, OSD, SDNR, DSS<br>WB(ATW/ATC/Manual), AGC, BLC, Flickerless                   | 399.02 |
| CNB-GN255    | GN255    | Standard Color Camera<br>1/3" SONY Super HAD CCD, 270K Pixels,<br>0.1 lx, AGC on/off, BLC on/off, AWB, DC/VIDEO Iris, C/CS Mount, 12VDC/24VAC Dual Voltage  | 168.08 |
| CNB-GN255DNF | GN255DNF | Standard Color Camera(Day&Night)<br>1/3" SONY Super HAD CCD, 270K Pixels,<br>0.1 lx(Day), 0.00 lx(IR LED on), AGC on/off, BLC on/off, AWB,<br>DC/VIDEO Iris, 12VDC/24VAC Dual Voltage                       | 184.24 |
| CNB-GN258    | GN258    | Standard Color Camera<br>1/3" SONY Super HAD CCD, 270K Pixels,<br>0.1 lx, AGC on/off, BLC on/off,<br>W/B auto/hold, DC/VIDEO Iris, 1 2VDV   | 151.34 |
| CNB-GN345    | GN345    | Standard Color Camera(480TVL)<br>1/3" SONY Super HAD CCD, 410K Pixels,<br>0.3 lx, AGC on/off, BLC on/off, DC/VIDEO Iris, Flickerless on/off, 12VDC/24VAC Dual Voltage                                       | 255.35 |

|              |          |  |         |
|--------------|----------|--|---------|
| CNB-GN355    | GN355    | Standard Color Camera(550TVL, DSS, SDNR, OSD)<br>1/3" SONY Super HAD CCD, 410K Pixels,<br>0.0003 lx, AGC, BLC, DC/VIDEO Iris, Flickerless on/off, DSS,<br>SDNR, OSD, DC12V   | 310.30  |
| CNB-GN605    | GN605    | WDR, D&N camera 1/3" SONY Double Scan CCD, 410K Pixels, C/CS Mount lens type, WDR, ICR(Motor D&N), OSD, DSS,<br>AC24V/DC1 2V   | 557.50  |
| CNB-GN785IR  | GN785IR  | Varifocal lens camera (550TVL, with IR LEDs, D&N)<br>1/3" SONY Super HAD CCD, 550TVL,<br>Vari-focal Lens(3.8~9.5mm), IR LEDs & Sensor<br>AWB, AGC On/Off, BLC On/Off, Flickerless On/Off,<br>D&N(ICR), SDNR, DSS On/Off, 2x Digital Zoom On/Off  | 466.61  |
| CNB-MN 1700  | MN 1700  | Miniature camera(32x32 Size)1/3" SONY CCD, 270K Pixels, 3.8 mm Fixed lens  | 127.73  |
| CNB-MN1310VD | MN1310VD | 550TVL Miniature camera(38x38 Size)1/3" SONY CCD, 410K Pixels, 4~9mm Vari-focal lens   | 313.54  |
| CNB-RBDS4812 | RBDS4812 | 480fps Capture Board (1 6CH, Recording 1 20fps)<br>Display/Recording FPS: 480fps/400fps(NTSC), 1 20fps/1 00fps(PAL)<br>Resolution: 320x240,720x480(NTSC), 320x288,720x576(PAL)<br>MPEG-4, Average Image Size 2KB, Network connection via TCP/IP<br>Audio Ch: 16 Line Level (optional Audio board)<br>16 Sensor In/8 Alarm Out via optional DIO board(DIO1 608) | 991.11  |
| CNB-RBDS4824 | RBDS4824 | 480fps Capture Board (16CH, Recording 240fps)<br>Display/Recording FPS: 480fps/400fps(NTSC), 240fps/200fps(PAL)<br>Resolution: 320x240,720x480(NTSC), 320x288,720x576(PAL)<br>MPEG-4, Average Image Size 2KB, Network connection via TCP/IP<br>Audio Ch: 16 Line Level (optional Audio board)<br>16 Sensor In/8 Alarm Out via optional DIO board(DIO1 608)     | 1130.50 |
| CNB-RBDS4848 | RBDS4848 | 480fps Capture Board (16CH, Recording 480fps)<br>Display/Recording FPS: 480fps/400fps(NTSC), 480fps/400fps(PAL)<br>Resolution: 320x240,720x480(NTSC), 320x288,720x576(PAL)<br>MPEG-4, Average Image Size 2KB, Network connection via TCP/IP<br>Audio Ch: 16 Line Level (optional Audio board)<br>16 Sensor In/8 Alarm Out via optional DIO board(DIO1 608)     | 1223.42 |
| CNB-S1265N   | S1265N   | 22x Indoor Speed Dome (480TVL)<br>1/4" SONY Super HAD CCD, 480TVL, 0.001 Lux(30IRE)<br>22x Optical Zoom(Digital 1 0x),<br>DSS, OSD, RS-485(Pelco-D/Pelco-P), Auto Flip/Parking<br>128 presets, 8 swings, 4 patterns, 8 groups<br>360? endless panning rotation, 24VAC  | 1736.86 |
| CNB-S1665NX  | S1665NX  | 18x Indoor Speed Dome (480TVL, EXview CCD, D&N)<br>1/4" SONY EXview HAD CCD, 480TVL, 0.01 Lux(50IRE)<br>18x Optical Zoom(Digital 12x), Day&Night(ICR),<br>DSS, OSD, RS-485(Pelco-D/Pelco-P), Auto Flip/Parking<br>128 presets, 8 swings, 4 patterns, 8 groups, Privacy Zone<br>360? endless panning rotation, 24VAC  | 2186.04 |
| CNB-S2265NP  | S2265NP  | 22x Outdoor Speed Dome (480TVL)<br>1/4" SONY Super HAD CCD, 480TVL, 0.001 Lux(30IRE)<br>22x Optical Zoom(Digital 1 0x),<br>DSS, OSD, RS-485(Pelco-D/Pelco-P), Auto Flip/Parking<br>128 presets, 8 swings, 4 patterns, 8 groups<br>360? endless panning rotation, 24VAC, Pendant mount  | 2066.26 |

|                |            |  |         |
|----------------|------------|--|---------|
| CNB-S2265NW    | S2265NW    | 22x Outdoor Speed Dome (480TVL)<br>1/4" SONY Super HAD CCD, 480TVL, 0.001 Lux(30IRE)<br>22x Optical Zoom(Digital 1 0x),<br>DSS, OSD, RS-485(Pelco-D/Pelco-P), Auto Flip/Parking<br>128 presets, 8 swings, 4 patterns, 8 groups<br>360? endless panning rotation, 24VAC, Wall mount   | 2126.15 |
| CNB-S2465NXP   | S2465NXP   | 26x Outdoor Speed Dome (480TVL, EXview CCD, D&N)<br>1/4" SONY EXview HAD CCD, 480TVL, 0.01 Lux(50IRE)<br>26x Optical Zoom(Digital 1 2x), Day&Night(ICR),<br>DSS, OSD, RS-485(Pelco-D/Pelco-P), Auto Flip/Parking<br>128 presets, 8 swings, 4 patterns, 8 groups, Privacy Zone<br>360? endless panning rotation, 24VAC, Pendant mount | 2869.75 |
| CNB-S2465NXW   | S2465NXW   | 26x Outdoor Speed Dome (480TVL, EXview CCD, D&N)<br>1/4" SONY EXview HAD CCD, 480TVL, 0.01 Lux(50IRE)<br>26x Optical Zoom(Digital 1 2x), Day&Night(ICR),<br>DSS, OSD, RS-485(Pelco-D/Pelco-P), Auto Flip/Parking<br>128 presets, 8 swings, 4 patterns, 8 groups, Privacy Zone<br>360? endless panning rotation, 24VAC, Wall mount    | 2928.92 |
| CNB-S2565NXP   | S2565NXP   | 30x Outdoor Speed Dome (480TVL, EXview CCD, D&N)<br>1/4" SONY EXview HAD CCD, 480TVL, 0.0005Lux(30IRE)<br>30x Optical Zoom(Digital 1 0x), Day&Night(ICR),<br>DSS, OSD, RS-485(Pelco-D/Pelco-P), Auto Flip/Parking<br>128 presets, 8 swings, 4 patterns, 8 groups<br>360? endless panning rotation, 24VAC, Pendant mount              | 2395.66 |
| CNB-S2565NXW   | S2565NXW   | 30x Outdoor Speed Dome (480TVL, EXview CCD, D&N)<br>1/4" SONY EXview HAD CCD, 480TVL, 0.0005Lux(30IRE)<br>30x Optical Zoom(Digital 1 0x), Day&Night(ICR),<br>DSS, OSD, RS-485(Pelco-D/Pelco-P), Auto Flip/Parking<br>128 presets, 8 swings, 4 patterns, 8 groups<br>360? endless panning rotation, 24VAC, Wall mount                 | 2455.56 |
| CNB-S2665NXP   | S2665NXP   | 1 8x Outdoor Speed Dome (480TVL, EXview CCD, D&N)<br>1/4" SONY EXview HAD CCD, 480TVL, 0.01 Lux(50IRE)<br>18x Optical Zoom(Digital 12x), Day&Night(ICR),<br>DSS, OSD, RS-485(Pelco-D/Pelco-P), Auto Flip/Parking<br>128 presets, 8 swings, 4 patterns, 8 groups, Privacy Zone<br>360? endless panning rotation, 24VAC, Pendant mount | 2485.50 |
| CNB-S2665NXW   | S2665NXW   | 1 8x Outdoor Speed Dome (480TVL, EXview CCD, D&N)<br>1/4" SONY EXview HAD CCD, 480TVL, 0.01 Lux(50IRE)<br>18x Optical Zoom(Digital 12x), Day&Night(ICR),<br>DSS, OSD, RS-485(Pelco-D/Pelco-P), Auto Flip/Parking<br>128 presets, 8 swings, 4 patterns, 8 groups, Privacy Zone<br>360? endless panning rotation, 24VAC, Wall mount    | 2545.39 |
| CNB-SCB2000    | SCB2000    | Corner mount for Indoor/Outdoor Speed Dome   | 226.26  |
| CNB-SD1700N    | SD1700N    | 380TVL Smoke Detector type camera(38x38 Size)1/3" SONY CCD, 270K Pixels, 3.8mm Fixed , DC12V   | 144.76  |
| CNB-SDF1212160 | SDF1212160 | Stand-alone DVR System (1 20fps, 4CH)<br>MPEG-4, Real-time Recording, Triplex, 4Ch Video Input,<br>Video Out(1 Composite BNC, 1 VGA), 4Ch Audio Recording<br>RTOS, Serial Port(RS-232C, RS-485), DDNS, 10/100-base T Ethernet<br>Resolution: 360x240,720x480(NTSC), 360x288,720x576(PAL) 160GB HDD                                   | 1161.47 |

|                   |               |   |         |
|-------------------|---------------|---|---------|
| CNB-SDF1212250    | SDF1212250    | Stand-alone DVR System (1 20fps, 4CH)<br>MPEG-4, Real-time Recording, Triplex, 4Ch Video Input,<br>Video Out(1 Composite BNC, 1 VGA), 4Ch Audio Recording<br>RTOS, Serial Port(RS-232C, RS-485), DDNS, 10/100-base T Ethernet<br>Resolution: 360x240,720x480(NTSC), 360x288,720x576(PAL) 250GB HDD  | 1204.83 |
| CNB-SDF1212400    | SDF1212400    | Stand-alone DVR System (1 20fps, 4CH)<br>MPEG-4, Real-time Recording, Triplex, 4Ch Video Input,<br>Video Out(1 Composite BNC, 1 VGA), 4Ch Audio Recording<br>RTOS, Serial Port(RS-232C, RS-485), DDNS, 10/100-base T Ethernet<br>Resolution: 360x240,720x480(NTSC), 360x288,720x576(PAL) 400GB HDD  | 1557.18 |
| CNB-SDF1212B      | SDF1212B      | Stand-alone DVR System (120fps, 4CH)<br>MPEG-4, Real-time Recording, Triplex, 4Ch Video Input,<br>Video Out(1 Composite BNC, 1 VGA), 4Ch Audio Recording<br>RTOS, Serial Port(RS-232C, RS-485), DDNS, 10/100-base T Ethernet<br>Resolution: 360x240,720x480(NTSC), 360x288,720x576(PAL) NO HDD  | 913.69  |
| CNB-SDF1212CD250  | SDF1212CD250  | Stand-alone DVR System (120fps, 4CH)<br>MPEG-4, Real-time Recording, Triplex, 4Ch Video Input,<br>Video Out(1 Composite BNC, 1 VGA), 4Ch Audio Recording<br>RTOS, Serial Port(RS-232C, RS-485/422), DDNS, 10/100-base T Ethernet<br>Resolution: 352x240, 704x480(NTSC), 352x288, 704x576(PAL) CDRW, 250GB HDD                                     | 1420.19 |
| CNB-SDF1212CD500  | SDF1212CD500  | Stand-alone DVR System (1 20fps, 4CH)<br>MPEG-4, Real-time Recording, Triplex, 4Ch Video Input,<br>Video Out(1 Composite BNC, 1 VGA), 4Ch Audio Recording<br>RTOS, Serial Port(RS-232C, RS-485/422), DDNS, 10/100-base T Ethernet<br>Resolution: 352x240, 704x480(NTSC), 352x288, 704x576(PAL) CDRW, 500GB HDD                                    | 1856.64 |
| CNB-SDF1212CDB    | SDF1212CDB    | Stand-alone DVR System (1 20fps, 4CH)<br>MPEG-4, Real-time Recording, Triplex, 4Ch Video Input,<br>Video Out(1 Composite BNC, 1 VGA), 4Ch Audio Recording<br>RTOS, Serial Port(RS-232C, RS-485/422), DDNS, 10/100-base T Ethernet<br>Resolution: 352x240, 704x480(NTSC), 352x288, 704x576(PAL) CDRW, NO HDD                                       | 1145.97 |
| CNB-SDN2712CD1000 | SDN2712CD1000 | Stand-alone DVR System (120fps, 9CH)<br>MPEG-4, Recording Max. 120(100)fps, Triplex, 9Ch Video Input,<br>Video Out(1 Composite BNC, 1 VGA, 1 S-Video), 4Ch Audio Recording<br>RTOS, Serial Port(RS-232C, RS-485/422), DDNS, 10/100-base T Ethernet<br>Resolution: 352x240, 704x240, 704x480(NTSC), 352x288, 704x288 704x576(PAL) CDRW, 1000GB HDD | 3386.88 |
| CNB-SDN2712CD1500 | SDN2712CD1500 | Stand-alone DVR System (120fps, 9CH)<br>MPEG-4, Recording Max. 120(100)fps, Triplex, 9Ch Video Input,<br>Video Out(1 Composite BNC, 1 VGA, 1 S-Video), 4Ch Audio Recording-RTOS, Serial Port(RS-232C, RS-485/422), DDNS,<br>10/100-base T Ethernet-Resolution: 352x240, 704x240, 704x480(NTSC), 352x288, 704x288 704x576(PAL)CDRW, 1500GB<br>HDD  | 4169.93 |

|                    |                |  |         |
|--------------------|----------------|--|---------|
| CNB-SDN2712CD250   | SDN2712CD250   | Stand-alone DVR System (1 20fps, 9CH)<br>MPEG-4, Recording Max. 120(100)fps, Triplex, 9Ch Video Input,<br>Video Out(1 Composite BNC, 1 VGA, 1 S-Video), 4Ch Audio Recording<br>RTOS, Serial Port(RS-232C, RS-485/422), DDNS, 10/100-base T Ethernet<br>Resolution: 352x240, 704x240, 704x480(NTSC), 352x288, 704x288 704x576(PAL) CDRW, 250GB HDD    | 2036.31 |
| CNB-SDN2712CD500   | SDN2712CD500   | Stand-alone DVR System (1 20fps, 9CH)<br>MPEG-4, Recording Max. 120(100)fps, Triplex, 9Ch Video Input,<br>Video Out(1 Composite BNC, 1 VGA, 1 S-Video), 4Ch Audio Recording<br>RTOS, Serial Port(RS-232C, RS-485/422), DDNS, 10/100-base T Ethernet<br>Resolution: 352x240, 704x240, 704x480(NTSC), 352x288, 704x288 704x576(PAL) CDRW, 500GB HDD    | 2515.45 |
| CNB-SDN2712CD750   | SDN2712CD750   | Stand-alone DVR System (1 20fps, 9CH)<br>MPEG-4, Recording Max. 120(100)fps, Triplex, 9Ch Video Input,<br>Video Out(1 Composite BNC, 1 VGA, 1 S-Video), 4Ch Audio Recording<br>RTOS, Serial Port(RS-232C, RS-485/422), DDNS, 10/100-base T Ethernet<br>Resolution: 352x240, 704x240, 704x480(NTSC), 352x288, 704x288 704x576(PAL)CDRW, 750GB HDD     | 2810.58 |
| CNB-SDN2712CDB     | SDN2712CDB     | Stand-alone DVR System (1 20fps, 9CH)<br>MPEG-4, Recording Max. 120(100)fps, Triplex, 9Ch Video Input,<br>Video Out(1 Composite BNC, 1 VGA, 1 S-Video), 4Ch Audio Recording<br>RTOS, Serial Port(RS-232C, RS-485/422), DDNS, 10/100-base T Ethernet<br>Resolution: 352x240, 704x240, 704x480(NTSC), 352x288, 704x288 704x576(PAL)CDRW, NO HDD        | 1736.86 |
| CNB-SDS4812CD 1500 | SDS4812CD 1500 | Stand-alone DVR System (1 20fps, 1 6CH)<br>MPEG-4, Recording Max. 120(100)fps, Triplex, 16Ch Video Input, Video Out(1 Composite BNC, 1 VGA, 1 S-Video), 4Ch Audio<br>Recording-RTOS, Serial Port(RS-232C, RS-485/422), DDNS, 10/100-base T Ethernet-Resolution: 352x240, 704x240,<br>704x480(NTSC), 352x288, 704x288 704x576(PAL)CDRW, 1500GB HDD    | 4342.48 |
| CNB-SDS4812CD1000  | SDS4812CD1000  | Stand-alone DVR System (1 20fps, 1 6CH) MPEG-4, Recording Max. 120(1 00)fps, Triplex, 1 6Ch Video Input, Video Out(1<br>Composite BNC, 1 VGA, 1 S-Video), 4Ch Audio Recording-RTOS, Serial Port(RS-232C, RS-485/422), DDNS, 10/100-base T<br>Ethernet-Resolution: 352x240, 704x240, 704x480(NTSC), 352x288, 704x288 704x576(PAL)CDRW, 1000GB HDD     | 3563.59 |
| CNB-SDS4812CD250   | SDS4812CD250   | Stand-alone DVR System (1 20fps, 1 6CH)<br>MPEG-4, Recording Max. 120(100)fps, Triplex, 16Ch Video Input,<br>Video Out(1 Composite BNC, 1 VGA, 1 S-Video), 4Ch Audio Recording<br>RTOS, Serial Port(RS-232C, RS-485/422), DDNS, 10/100-base T Ethernet<br>Resolution: 352x240, 704x240, 704x480(NTSC), 352x288, 704x288 704x576(PAL) CDRW, 250GB HDD | 2215.99 |
| CNB-SDS4812CD500   | SDS4812CD500   | Stand-alone DVR System (1 20fps, 1 6CH)<br>MPEG-4, Recording Max. 120(100)fps, Triplex, 16Ch Video Input,<br>Video Out(1 Composite BNC, 1 VGA, 1 S-Video), 4Ch Audio Recording<br>RTOS, Serial Port(RS-232C, RS-485/422), DDNS, 10/100-base T Ethernet<br>Resolution: 352x240, 704x240, 704x480(NTSC), 352x288, 704x288 704x576(PAL) CDRW, 500GB HDD | 2695.12 |
| CNB-SDS4812CD750   | SDS4812CD750   | Stand-alone DVR System (1 20fps, 1 6CH)<br>MPEG-4, Recording Max. 120(100)fps, Triplex, 16Ch Video Input,<br>Video Out(1 Composite BNC, 1 VGA, 1 S-Video), 4Ch Audio Recording<br>RTOS, Serial Port(RS-232C, RS-485/422), DDNS, 10/100-base T Ethernet<br>Resolution: 352x240, 704x240, 704x480(NTSC), 352x288, 704x288 704x576(PAL) CDRW, 750GB HDD | 2974.56 |

|                |            |  |         |
|----------------|------------|--|---------|
| CNB-SDS4812CDB | SDS4812CDB | Stand-alone DVR System (120fps, 16CH)<br>MPEG-4, Recording Max. 120(100)fps, Triplex, 16Ch Video Input,<br>Video Out(1 Composite BNC, 1 VGA, 1 S-Video), 4Ch Audio Recording<br>RTOS, Serial Port(RS-232C, RS-485/422), DDNS, 10/100-base T Ethernet<br>Resolution: 352x240, 704x240, 704x480(NTSC), 352x288, 704x288 704x576(PAL) CDRW, NO HDD  | 1916.53 |
| CNB-SIB1000    | SIB1000    | In-Ceiling mount bracket for Indoor Speed Dome   | 177.78  |
| CNB-SM1063N    | SM1063N    | 10x Mini Indoor Speed Dome (500TVL, EXview CCD), DC12V<br>1/4" SONY Super HAD CCD, 550TVL, 0.005Lux,<br>10x Optical Zoom(Digital 10x), Day&Night(ICR),<br>DSS, OSD, RS-485(Pelco-D/Pelco-P), Auto Flip/Parking<br>128 presets, 8 swings, 4 patterns, 8 groups, Privacy Zone<br>360? endless panning rotation   | 1300.83 |
| CNB-SN258IR    | SN258IR    | Sensor-Cam<br>1/3" SONY Super HAD CCD, 270K Pixels,<br>3.8mm lens, DC1 2V, 11 LEDs, 1 CdS Sensor,<br>Visibility Range : 5 meter (940 nm, 20 degree)  | 232.73  |
| CNB-SOB2000    | SOB2000    | Pole mount for Indoor/Outdoor Speed Dome   | 193.94  |
| CNB-SPB1000    | SPB1000    | Pendant mount bracket for Indoor Speed Dome  | 177.78  |
| CNB-SSS2000    | SSS2000    | Sun shield for Outdoor Speed Dome  | 148.05  |
| CNB-SWB1000    | SWB1000    | Wall mount bracket for Indoor Speed Dome   | 177.78  |
| CNB-V1000N     | V1000N     | Vandal Proof Dome camera(3-Axis, Surface Mount)<br>1/3" SONY Super HAD CCD, 270K Pixels, 0.1 lx, 3.8 mm lens<br>AWB, AGC On/off, BLC On/off, Service Video Out,<br>100mm dome size, DC1 2V   | 219.80  |
| CNB-V1000NIR   | V1000NIR   | Vandal Proof IR Dome camera(380TVL, Surface Mount)<br>1/3" SONY CCD, 3.8mm lens, 24 LEDs, 1 CdS Sensor, DC12V, Visibility Range : 850 nm, 30 degree(10 meter)  | 277.98  |
| CNB-V1000NVD   | V1000NVD   | Vandal Proof Dome camera(3-Axis, Surface Mount)<br>1/3" SON Super HADY CCD, 270K Pixels, 0.1 lx, Vari focal Lens(4-9mm), Auto white balance, AGC On/off, BLC On/off, Service<br>Video Out, 100mm dome size, DC12V  | 297.37  |
| CNB-V1310N     | V1310N     | Vandal Proof Dome camera(3-Axis, Surface Mount, 550TVL)<br>1/3" SON Super HADY CCD, 410K Pixels, 0.1 lx, 3.8mm Fixed Lens, Auto white balance, AGC On/off, BLC On/off, Service<br>Video Out, 100mm dome size, DC12V  | 313.54  |
| CNB-V1310NIR   | V1310NIR   | Vandal Proof IR Dome camera(550TVL, Surface Mount)<br>1/3" SONY CCD, 3.8mm lens, 24 LEDs, 1 CdS Sensor, DC12V, Visibility Range : 850 nm, 30 degree(10 meter)  | 357.20  |
| CNB-V1315NVD   | V1315NVD   | Vandal Proof Dome Camera(3-Axis, Surface Mount, 550TVL)<br>1/3" SONY Super HAD CCD, 550TVL, 410K Pixels, Vari-focal Lens(4-9mm), 0.3 Lux, AGC On/Off, BLC On/Off, Flickerless<br>On/Off, Service Video Out, Dome size : 100mm, 1 2VDC/24VAC Dual Voltage   | 411.89  |
| CNB-V1815NVR   | V1815NVR   | Vandal-Resistant IR Dome Camer (Surface Mount, 550TVL, SDNR, D&N, DSS, Vari-focal Lens)<br>1/3" SONY Super HAD CCD, 550TVL, SDNR, 0.00Lux(IR LED On)<br>AWB, AGC On/Off, BLC On/Off, Flickerless On/Off, D&N(ICR) On/Off, DSS On/Off, 2x Digital Zoom On/Off, 100mm dome size,<br>3-Axis, 20 LEDs, 1 CdS Sensor, IR LED's Visibility Range : 15 meter (850nm, 30?)<br>Service Extra-Video out, 1 2VDC, (Heater Optional) | 550.27  |
| CNB-V2000NDNF  | V2000NDNF  | Vandal Proof Dome camera(3-Axis, IR Filter Day&Night)<br>1/3" SONY CCD, 270K Pixels, 0.1 lx, Vari Focal lens(4-9mm),<br>AWB, AGC On/off, BLC On/off, Service Video Out,<br>100mm dome size, DC1 2V   | 242.42  |
| CNB-V2000NIR   | V2000NIR   | Vandal Proof IR Dome camera(380TVL)<br>1/3" SONY CCD, 3.8mm lens, 24 LEDs, 1 CdS Sensor, DC12V, Visibility Range : 850 nm, 30 degree(10 meter)   | 284.44  |

|              |          |   |        |
|--------------|----------|---|--------|
| CNB-V2265NVF | V2265NVF | Vandal Proof Dome Camera(3-Axis, WDR, ICR, OSD, DSS)<br>1/3" SONY Double Scan CCD, 410K Pixels, Vari-focal Lens(3.8~9.5mm),<br>0.001 Lux(Color), 0.0003 Lux(B/W), OSD, WDR On/Off,AGC On/Off,<br>BLC On/Off, Flickerless On/Off, Service Video Out, Dome size : 100mm, 1 2VDC/24VAC Dual Voltage  | 690.69 |
| CNB-V2310NIR | V2310NIR | Vandal Proof IR Dome camera(550TVL)<br>1/3" SONY CCD, 3.8mm lens, 24 LEDs, 1 CdS Sensor, DC12V, Visibility Range : 850 nm, 30 degree(10 meter)  | 370.07 |
| CNB-V2315NVD | V2315NVD | Vandal Proof Dome Camera(3-Axis, 550TVL)<br>1/3" SONY Super HAD CCD, 550TVL, 410K Pixels, Vari-focal Lens(4~9mm), 0.3 Lux, AGC On/Off, BLC On/Off, Flickerless<br>On/Off, Service Video Out, Dome size : 100mm, 1 2VDC/24VAC Dual Voltage   | 421.56 |
| CNB-V2315NVF | V2315NVF | Vandal Proof Dome Camera(3-Axis, 550TVL, Day&Night)<br>1/3" SONY Super HAD CCD, 550TVL, 410K Pixels, Vari-focal Lens(3.8~9.5mm), 0.3 Lux(Color), 0.05 Lux(B/W), AWC, AGC<br>On/Off, BLC On/Off, Flickerless On/Off, Service Video Out, Dome size : 100mm, 1 2VDC/24VAC Dual Voltage   | 482.68 |
| CNB-V2815NVD | V2815NVD | Vandal Proof Dome Camera(3-Axis, 550TVL, DSS, SDNR)<br>1/3" SONY Super HAD CCD, 550TVL, 410K Pixels, Vari-focal Lens(4-9mm), 0.001 Lux, AGC On/Off, BLC On/Off, Flickerless<br>On/Off, DSS, SDNR, Service Video Out, Dome size : 100mm, 1 2VDC/24VAC Dual Voltage   | 444.07 |
| CNB-V2815NVF | V2815NVF | Vandal Proof Dome Camera(3-Axis, 550TVL, Day&Night, DSS, SDNR)<br>1/3" SONY Super HAD CCD, 550TVL, 410K Pixels, Vari-focal Lens(3.8~9.5mm), 0.0003 Lux, AWC, AGC On/Off, BLC On/Off,<br>Flickerless On/Off, DSS, SDNR, Service Video Out, 1 2VDC/24VAC Dual Voltage, Dome size : 100mm  | 505.22 |
| CNB-V2815NVR | V2815NVR | Vandal-Resistant IR Dome Camer (550TVL, SDNR, D&N, DSS, Vari-focal Lens)<br>1/3" SONY Super HAD CCD, 550TVL, SDNR, 0.00Lux(IR LED On)<br>AWB, AGC On/Off, BLC On/Off, Flickerless On/Off, D&N(ICR) On/Off, DSS On/Off, 2x Digital Zoom On/Off, 100mm dome size,<br>3-Axis, 20 LEDs, 1 CdS Sensor, IR LED's Visibility Range : 15 meter (850nm, 30?)<br>Surface & Flush mount type, Service Extra-Video out, 1 2VDC, (Heater Optional) | 563.15 |
| CNB-V2965NVD | V2965NVD | Vandal-Resistant Dome Camera (530TVL, SDNR, OSD, DSS)<br>1/3" SONY Super HAD CCD, 530TVL, Color/BW<br>WB(ATW/ATC/Manual), AGC, BLC, Flickerless,<br>OSD, SDNR, DSS, Service Extra-Video out, 3-Axis,<br>100mm dome size, Surface & Flush mount type, Dual Voltage<br>(Heater Optional)  | 453.74 |
| CNB-V3710N   | V3710N   | Dome Camera(85mm Dome Size)<br>SONY Super HAD CCD, 480TVL, 410K Pixels, 3.8mm, 0.3 Lux,<br>AWC, AGC On/Off, BLC On/Off, Flickerless On/Off, Service Video Out, Dome size : 85mm, DC1 2V   | 248.89 |
| CNB-V4710N   | V4710N   | Dome Camera (3-Axis, Surface Mount)<br>1/3" SONY Super HAD CCD, 480TVL, 410K Pixels,<br>3.8mm, 0.3 Lux, AWC, AGC On/Off, BLC On/Off, Flickerless On/Off,<br>Dome size : 68mm, DC1 2V  | 323.23 |
| CNB-V4711N   | V4711N   | Dome Camera (3-Axis, Flush Mount)<br>1/3" SONY Super HAD CCD, 480TVL, 410K Pixels,<br>3.8mm, 0.3 Lux, AWC, AGC On/Off, BLC On/Off, Flickerless On/Off,<br>Dome size : 68mm, DC1 2V  | 323.23 |
| CNB-VZD127NL | VZD127NL | 1 6x AF Zoom Dome Camera(With DSS)<br>1/4" SONY Super HAD CCD, 410k Pixels,<br>16x Zoom (Digital 12x), RS-485 Interface, Day&Nigh(Digital Slow Shutter), AC24V/DC12V Dual Voltage, Vandal Proof, Weather<br>Proof(IP65)   | 675.19 |
| CNB-VZD207NL | VZD207NL | 22x AF Zoom Dome Camera(With DSS)<br>1/4" SONY Super HAD CCD, 410k Pixels,<br>22x Zoom (Digital 10x), RS-485 Interface,Day&Nigh(Digital Slow Shutter), AC24V/DC12V Dual Voltage, Vandal Proof, Weather<br>Proof(IP65)   | 712.36 |
| CNB-WMB65    | WMB65    | Ceiling and Wall mount bracket for CNB Weather Proof IR Camera  | 11.26  |

|            |        |   |        |
|------------|--------|---|--------|
| CNB-WVB100 | WVB100 | Wall Mount Bracket for Vandal Proof Dome Camera | 113.93 |
|------------|--------|---|--------|